



Engineered Chemistries
SUPERIOR SOLUTIONS

MARINE CLEANER & DEGREASER

SEA - POWER 2X CONCENTRATED

**LOW AQUATIC TOXICITY -
LC50 GREATER THAN 10 PPM**

PHOSPHATE FREE

CAUSTIC FREE

NON-FLAMMABLE

**NON-EMULSIFYING -
Oil Water Separator Safe**

NPE/APE FREE (nonylphenols)

READILY BIODEGRADABLE

SCAN FOR
SDS



**Meets EPA NPDES Vessel
General Permit requirements
effective 12/19/13 - 2018.**

**KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL USE ONLY.
READ SAFETY DATA SHEET BEFORE USE.**

NET WEIGHT: U.S. GALLONS

1/23

VESSEL GENERAL PERMIT (VGP) ABOVE WATER LINE/DECK CLEANING

Vessel owner/operators must minimize the introduction of on-deck debris, garbage, residue, and spill into deck washdown and runoff discharges. Before deck washdowns occur, you must broom clean (or equivalent) exposed decks or use comparable management measures and remove all existing debris. The presence of floating solids, visible foam, halogenated phenol compounds, and dispersants, or surfactants in deck washdowns must be minimized. If deck washdowns or above water line hull cleaning will result in a discharge, they must be conducted with "minimally-toxic" and "phosphate free" cleaners and detergents as defined in Appendix A of this VGP (effective 12/19/13-2018).

DIRECTIONS FOR USE:

SEA-POWER Marine Cleaner & Degreaser can be used full-strength or diluted with water depending on the surface to be cleaned.

Above Waterline/Deck Cleaning: Apply **SEA-POWER Marine Cleaner & Degreaser** solution by spray, brush or mop onto surface to be cleaned. Allow time for **SEA-POWER Marine Cleaner & Degreaser** to penetrate grease, grime and other soils completely. Rinse thoroughly with water.

Bilge Cleaning: Apply **SEA-POWER Marine Cleaner & Degreaser** solution by spray, brush or mop onto surface to be cleaned. Allow time for **SEA-POWER Marine Cleaner & Degreaser** to penetrate grease, grime and other soils completely. Rinse thoroughly with water. Bilge slops can be sent directly to the (OWS) Oil/Water Separator immediately after cleaning. No waiting for oil/water separation is necessary.

FOR USE ON:

Bilges, Decks, Engines, Equipment, Hulls, Oil Platforms, OSV's, Pumps, Tugs, Barges, Etc.

FIRST AID

EYES: Flush with water for 15 minutes. Seek medical attention.

SKIN: Wash with soap and water. If irritated, seek medical attention.

INHALATION: Remove to fresh air. Resuscitate if necessary. Get medical attention.

INGESTION: Do not induce vomiting. Drink two large glasses of water. Get immediate medical attention.

PROPER PPE: B - Safety Glasses, Chemical/liquid Resistant Gloves

WARNING

Use personal protective equipment as required.
Causes mild skin irritation.
Causes eye irritation.
May be harmful if swallowed and enters airways.



WECHEM, INC.

5734 Susitna Dr · Harahan, LA 70123

(504) 733-1152 · 800-426-0512

FAX (504) 733-2218 · www.wechem.com



7 83583 28623 7