

DESCRIPTION

DYNAMIC GREEN is a heavy duty industrial and institutional cleaner. It quickly cuts through and lifts the toughest oils, greases, carbon deposits and all types of grime. Oilfield, industrial, marine, aircraft and municipal uses are virtually unlimited.

DYNAMIC GREEN may be used through all types of mechanical cleaning equipment including: steam cleaners, pressure washers and automatic scrubbing machines. It may also be used in manual cleaning operations including: spray on / flush off, bucket washing, mopping and scrubbing. The special lifting action of this product will allow for easy rinsing and equipment cleaning. Formulated for use with oil separators.

FOR USE ON: Bilges, Decks, Engines, Equipment, Pumps, Oil Platforms, OSV's, Tugs, Barges, Etc.

SPECIAL DILUTIONS

General Dilution Table

USES	CLEANER & DEGREASER	WATER (parts)
Light Cleaning	1 part	50 to 80
Medium Cleaning	1 part	10 to 60
Heavy Duty Cleaning	1 part	5 to 10
Extra Heavy Duty Cleaning	1 part	3 to 5

For Steam Cleaners and Pressure Washers

To the concentrate solution tank, add 4 to 14 ounces **DYNAMIC GREEN** to each gallon of water. Adjust the solution tank valve to obtain amount of cleaner required for different soil conditions.

For Automatic Scrubbers

Increase concentration of use dilution only enough to remove soil present. A 25 to 1 dilution with water is the recommended starting point.

Meets EPA NPDES Vessel General Permit requirements effective 12/19/13.

DYNAMIC GREEN[®]

CLEANER & DEGREASER

HEAVY DUTY INDUSTRIAL & INSTITUTIONAL CLEANER



ENVIRONMENTALLY PREFERRED

- **LOW AQUATIC TOXICITY**
- **PHOSPHATE FREE**
- **NON-EMULSIFYING**
- **READILY BIODEGRADABLE**

WARNING

**KEEP OUT OF REACH OF CHILDREN.
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.**
(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

NET CONTENTS: U.S. GALLON



WARNING

Causes mild skin irritation. Causes eye irritation. May cause respiratory irritation. May be harmful if swallowed and enters airways.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue Rinsing.

PROPER PPE: B-Safety Glasses, Chemical, Liquid Resistant Gloves

READ SAFETY DATA SHEET BEFORE USE.

VESSEL GENERAL PERMIT (VGP) ABOVE WATER LINE/DECK CLEANING

Vessel owner/operators must minimize the introduction of on-deck debris, garbage, residue, and spill into deck washdown and runoff discharges. Before deck washdowns occur, you must broom clean (or equivalent) exposed decks or use comparable management measures and remove all existing debris. The presence of floating solids, visible foam, halogenated phenol compounds, and dispersants, or surfactants in deck washdowns must be minimized.

If deck washdowns or above water line hull cleaning will result in a discharge, they must be conducted with "minimally-toxic" and "phosphate free" cleaners and detergents as defined in Appendix A of this VGP (effective 12/19/13).



Engineered Chemistries
SUPERIOR SOLUTIONS[®]

WECHEM, INC.

5734 Susitna Dr. • Harahan, LA 70123

504.733.1152 • 1.800.426.0512

FAX 504.733.2218 • www.wechem.com

SCAN FOR SDS

