

DESCRIPTION

HV-500 is a high alkaline stripping compound formulated for heavy-duty industrial use. It removes grease, oil, paint, rust and carbonized soils from a wide variety of steel and iron parts. This high intensity alkaline product contains buffered wetting agents that remain strong and stable under high temperatures over long periods of time. It also contains corrosion inhibitors to prevent flash rusting of parts once they are removed from your tank. Not for use on aluminum or yellow metal parts.

DIRECTIONS

Average concentration is 6 to 8 ounces of **HV-500** per gallon of water (45 to 60 grams per liter). For de-rusting and paint stripping, use near boiling temperatures, 160° to 200°F. Add compound as needed (**SLOWLY and CAREFULLY**) to avoid boil-over and splashing. Do not air agitate. Use a plastic bristle brush to loosen caked grime and paint. Rinse thoroughly.



Engineered Chemistries
SUPERIOR SOLUTIONS

HV-500™

Hot Vat Compound

DE-RUSTING ACTION

STRIPS OFF PAINT

DISSOLVES GREASE

BIODEGRADABLE

DANGER: CORROSIVE
KEEP OUT OF REACH OF CHILDREN.
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.
(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

NET CONTENTS: 400 LBS

1/22



DANGER: CORROSIVE

May be corrosive to metals. May be harmful if swallowed. May be harmful in contact with skin. Causes severe skin burns and eye damage. Cause eye irritation. May cause damage to organs. Harmful to aquatic life.

Keep out of reach of children. Read label before use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Absorb spillage to prevent material damage. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Store locked up. Store in a corrosive resistant container with a resistant inner liner. Dispose of content/container in accordance with local, regional, national and international regulations.

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice/attention.

Proper Shipping Name: UN 1823, Corrosive Material, n.o.s., 8, PG II (Sodium Hydroxide)

READ SAFETY DATA SHEET BEFORE USE.

WECHEM, INC.
5734 Susitna Dr
Harahan, LA 70123
(504) 733-1152
800-426-0512
FAX (504) 733-2218
WWW.WECHEM.COM

