

Removes a Wide Range of Paints, Gaskets, and Graffiti from Metal, Concrete and Wood.

PGS is a gel-based paint remover quickly removes paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials. Product will not run. The methylene chloride free formula is a safer alternative to paint removal.

FOR USE BY: Auto dealers, paint shops, maintenance departments, engine rebuilders, factories, furniture refinishers, painters, sign builders, schools, motels, hotels, hospitals and offices.

FOR USE ON: Metal parts, plaster, concrete, tile, glass, ceramic, engine parts, valve seals, paint guns, paper, wood, stone, masonry and cylinders.



Engineered Chemistries
SUPERIOR SOLUTIONS

PGS

PAINT & GASKET STRIPPER



DANGER

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents / container in accordance with local / regional / national / international regulations

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.

IN ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF EXPOSED OR CONCERNED: Get medical advice/attention.

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Contains: Methanol (67-56-1).

May be fatal or cause blindness if swallowed.

READ SAFETY DATA SHEET BEFORE USE.

DIRECTIONS:

Shake well before using. Holding can eight to ten inches from surface to be treated, apply a medium to heavy coat on surface as needed. A thicker application will speed up action. Blistering will occur in three or four minutes, but may take up to twenty minutes, depending on material being treated. Allow product to complete blistering before removing.

METHYLENE CHLORIDE FREE MULTI-SURFACE

DANGER:

**EXTREMELY FLAMMABLE AEROSOL.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.**

KEEP OUT OF REACH FROM CHILDREN.


(See right panel for additional cautions)

NET WT. 11 OZ. (312 g)

CONTAINS (CAS#): Acetone (67-64-1), Dioxolane (646-06-0), Propane/n-Butane (68476-86-8), Monoethanolamine (141-43-5), Isopropylidene Glycol (100-79-8).



SCAN FOR SDS



WEICHEM, INC.
5734 Susitna Dr. • Harahan, LA 70123
504.733.1152 • 1.800.426.0512
FAX 504.733.2218 • www.wechem.com

Item #A65 Rev. 09.2024