



**EMERGENCY TELEPHONE:
INFOTRAC 1-866-836-8855**

WARNING: Flammable liquid and vapor. May cause respiratory irritation. May cause drowsiness or dizziness. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapors. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Use only outdoors or in a well ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulation.

FIRST AID: IF SWALLOWED: immediately call a poison center/doctor. Do NOT induce vomiting.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF EXPOSED OR CONCERNED: get medical advice/attention. **IF IN EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

IF INHALED: Move to fresh air. Call a physician if symptoms develop or persist.

CONTAINS (CAS No.): Distillates, petroleum, hydrotreated light (64742-47-8) and Sulfonic acids, petroleum, sodium salts (68608-26-4).

SCAN FOR SDS



FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY



Engineered Chemistries
SUPERIOR SOLUTIONS

PROTECTO FLEX™

METAL PARTS PROTECTOR

**Non-Chlorinated
Long-term Flexible
Non-Tacky
Corrosion Preventative
Easily Removable**

WARNING:

**FLAMMABLE LIQUID AND VAPOR.
KEEP OUT OF REACH OF CHILDREN.
SEE SIDE PANEL FOR PRECAUTIONS.**

NET CONTENTS: U.S. GALLON

A revolutionary, non-greasy, non-dirt collection, nontacky, dust retardant, continuous flexible film that will not crack, peel, flake or check with a temperature range of -40°F to +175°F.

Protects all metals against atmospheric rust and corrosion, salt spray, high humidity, chemical fumes, abrasion matter, fingerprinting and fingerprint corrosion.

Coating is translucent, allowing part numbers and identification codes to be easily read. Easily removed with solvent versus hard-to-remove cosmoline.

USES: Machinery and metal parts – especially those in storage both indoors and outdoors, marine equipment, storage of tools, drills, etc. – especially around outdoor drilling operations, farm and road machinery, finished or fabricated castings, valves, stampings, housings – especially in packaged equipment or parts in transit and during domestic or overseas shipments.

DIRECTIONS:

1. For best action and fullest protection, first clean object by removing rust, dirt, grease, oil and debris. This will also promote the container from being contaminated if used as a dip tank treatment.
2. Apply by brush, mop, spray or dip.
3. When dipping, allow parts to be immersed for several minutes, remove and allow the solvent base to evaporate.
4. When spraying, spray an even coat over entire surface and allow to dry.
5. For more severe storage or for protection against more harmful conditions, a second coat can be applied within several minutes.
6. Complete setting of protective coating takes at least two hours.
7. Film can be easily removed with rag wet with mineral spirits or safety solvent degreaser.

WEICHEM, INC.
5734 Susitna Dr.
Harahan, LA 70123
(504) 733-1152 | (800) 426-0512
FAX (504) 733-2218
www.wechem.com



7 38435 20686 4