

GHS Safety Data Sheet

Wechem, Inc.

Hulk System FS 250 (RTU)

MSDS Number: HFS250RTUC Revision Date: 11/24/2014

> Page 1 **of** 6

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Wechem, Inc 5734 Susitna Dr Harahan, LA 70123

Contact: Ligia M. Hernandez Phone: 504-733-1152 Fax: 504-733-2218 Web: www.wechem.com

Product Name: Hulk System FS 250 (RTU)

Revision Date: 11/24/2014 **MSDS Number:** HFS250RTUC **Product Code:** HFS250

Product Use: Industrial Cleaner / Degreaser

Emergency Telephone Number:

INFOTRAC 1-800-535-5053

HAZARDS IDENTIFICATION

Route of Entry: Skin absorption, ingestion, inhalation, eye

Target Organs:

Inhalation: Inhalation of generated mist can cause nasal and respiratory irritation or damage to respiratory tract.

Skin Contact: Corrosive. Causes irritation **Eye Contact:** Causes irritation and burning

Corrosive. Harmful or fatal if swallowed. Ingestion:

PERSONAL PROTECTION INDEX							
Α	80	G	Ø⊠+ = +₩				
В	Ø Ø + ● €	Н	□ + = + 1 + *				
С	Ø Ø + ● + ♣	I	∞4 * + *				
D	⊕ + ■ + †	J	□ +•++*				
Ε	Ø ∀ + ■ + ②	K	₹ + + ↑ + L				
F ∞ + + + + + 			Consult your supervisor or S.O.P. for "SPECIAL" handling directions				
A Safety Glasses	Splash Goggles Splash Goggles Splash Face Shield & Eye Protection Glove	*	9 L r Synthelic Apron Suit				
t Dust Respira	Vapor Respirator Respirator Property National Pr	ice vator	Airline Hood or Mesk				



GHS Safety Data Sheet

Wechem, Inc.

Hulk System FS 250 (RTU)

MSDS Number: HFS250RTUC Revision Date: 11/24/2014

Page 2 of 6

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:





GHS Classifications:

Health, Acute toxicity, 4 Oral

Health, Skin corrosion/irritation, 1 B

Health, Specific target organ toxicity - Single exposure, 3

GHS Phrases:

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

GHS Precautionary Statements:

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P363 - Wash contaminated clothing before reuse.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P304+312 - IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P311 - Call a POISON CENTER or doctor/physician.

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Chemical Name	Perc.	OSHA PEL ACGIH Carcin. (ppm) TLV(ppm) Ref.		
1310-58-3	Potassium hydroxide (K(OH))	<3%	2mg/m3	2mg/m3	D
N/A	Surfactant Blend	Trade Secret	NA	NA	D



GHS Safety Data Sheet

Wechem, Inc.

Hulk System FS 250 (RTU)

MSDS Number: HFS250RTUC Revision Date: 11/24/2014

> Page 3

FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical

advice/attention.

Skin Contact: Immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse.

Get medical advice/attention.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get

immediate medical advice/attention.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an

unconscious person. Get immediate medical advice/attention.

FIRE FIGHTING MEASURES

Flammability: Not Flammable by OSHA criteria

Flash Point: > 200 Deg. F.

Burning Rate: ND **Autoignition Temp:** ND LEL: ND **UEL:** ND

Extinguishing media: Foam, dry chemical, carbon dioxide, water

Special fire fighting procedures: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA)

Unusual Fire & Explosion Hazards: None known

ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Avoid any contact with the skin and eyes.

Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Scoop up material and place in a disposal container. Provide ventilation.

HANDLING AND STORAGE

Handling Precautions: Corrosive liquid. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Do not get in

eyes, on skin, or on clothing. Do not swallow. Handle and open container with care. When using do not

eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practices.

Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

Storage Requirements: Corrosive liquid. Handle all containers carefully. Keep out of reach of children.

Keep container tightly closed and in a well-ventilated place. Store locked up.



GHS Safety Data Sheet

Wechem, Inc.

Hulk System FS 250 (RTU)

MSDS Number: HFS250RTUC Revision Date: 11/24/2014

Page 4 of 6

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Personal Protective Equip: HMIS PP, B | Goggles, Gloves

Respiratory Protection: None required under normal use conditions.

Protective gloves: Chemical resistant, rubber, PVC

Eye protection: Safety glasses/goggles

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, red Physical State: Liquid

Physical State: Liquid Odor:
Particle Size: NA Molecular F

Spec Grav./Density: (H20=1): 1.1 +/- 0.1

Viscosity:NASat. Vap. Conc.:NABoiling Point:212 Deg. F.Flammability:Not Flammable

Vapor Pressure: ND > 12

Evap. Rate: NA Molecular weight: NA

Odor: Characteristic

Molecular Formula: NA
Solubility: Complete
Softening Point: NA
Percent Volatile: NA
Heat Value: NA
Freezing/Melting Pt.: NA

Flash Point: > 200 Deg. F.

Octanol: NA

Vapor Density: (Air=1): ND

VOC: NA
Bulk Density: NA

10 STABILITY AND REACTIVITY

Stability: Stable under normal conditions of use.

Conditions to Avoid: Incompatible materials.

Materials to Avoid: Strong oxidizers, acids

Hazardous Decomposition: Carbon dioxide, carbon monoxide

Hazardous Polymerization: Will not occur



GHS Safety Data Sheet

Wechem, Inc.

Hulk System FS 250 (RTU)

MSDS Number: HFS250RTUC Revision Date: 11/24/2014

Page 5 of 6

TOXICOLOGICAL INFORMATION

Data for the components of this material is summarized as follows:

```
Potassium hydroxide (K(OH))
                                    (1310-58-3)
Oral- LD50 214 mg/kg (Rat)
Surfactant Blend
                                      (CAS# NA)
Oral- LD50 2700 mg/kg (Mouse)
Oral- LD50 1064-16800 mg/kg (Rat)
Dermal- LD50 >2000 mg/kg (Rabbit)
```

ECOLOGICAL INFORMATION

Data for the components of this material is summarized as follows: Aquatic Toxicity:

Surfactant Blend (CAS# NA) EC50 Algae: 0.19 mg/l 72 hr EC50 Daphnia 3.1 mg/l 48 hr LC50 Fish 2.67 mg/l 96 hr LC50= 60.6 mg/l (96 h) Fathead Minnow (Pimephales promelas) LC50= 100-250 mg/l (24 h) Fathead Minnow (Pimephales promelas)

This product is inherently biodegradable.

DISPOSAL CONSIDERATIONS

Dispose of according to local, state, or federal regulations.

TRANSPORT INFORMATION

Proper Shipping Name: NA 1760, Compounds, Cleaning liquid, (Potassium Hydroxide), 8, PG II



GHS Safety Data Sheet

Wechem, Inc.

Hulk System FS 250 (RTU)

MSDS Number: HFS250RTUC Revision Date: 11/24/2014

Page 6 of 6

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Potassium hydroxide (K(OH)) (1310583 <3%) CERCLA, CSWHS, MASS, OSHAWAC, PA, TSCA, TXAIR

*Surfactant Blend (CAS# Trade Secret) TSCA

REGULATORY KEY DESCRIPTIONS

CERCLA = Superfund clean up substance CSWHS = Clean Water Act Hazardous substances MASS = MA Massachusetts Hazardous Substances List OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TXAIR = TX Air Contaminants with Health Effects Screening Level TSCA = Toxic Substances Control Act

OTHER INFORMATION

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. ** Chemical listed as carcinogen or potential carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not listed [e] Animal Data only N/A = Not available N/D = Not determined