

**C-130** cools threads and pipe during operation thereby improving thread quality!

**C-130's** clear, light color allows operators to better see the machined part during the cutting operation. It has a low odor and contains an ISOSYN base stock, which provides better thermal and oxidation stability for longer fluid life. The ISOSYN base stock also increases oil life and creates a safer work environment by increasing the fluid's flash point and lowering exposure to aromatics and product vapor, smoking and misting. The chlorine-free nature of the fluid reduces the cost of disposal at the end of the fluid life.

WECHEM, INC.  
5734 Susitna Dr • Harahan, LA 70123  
(504) 733-1152 • 800-426-0512  
FAX (504) 733-2218 • WWW.WECHEM.COM



# C-130™

CUTTING AND  
THREADING OIL



- **READY TO USE FORMULA**
- **ANTI-CORROSIVE**
- **COOLS AND LUBRICATES**

## WARNING

**KEEP OUT OF REACH OF CHILDREN**  
FOR INDUSTRIAL USE ONLY  
SEE RIGHT PANEL FOR ADDITIONAL PRECAUTIONS AND FIRST AID STATEMENTS.

Net Contents: U.S. GALLON

Rev. 02.2024



## WARNING

Causes mild skin irritation. Causes eye irritation. May cause respiratory irritation.

Ground/bond container and receiving equipment. Do not breathe mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Avoid release to the environment.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or a rash occurs: Get medical attention.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Get medical advice/attention.

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention

READ SAFETY DATA SHEET BEFORE USE.

Proper Shipping Name: Petroleum Oils, Greases

SCAN FOR SDS

