

Hulk System # 103ES

MSDS Number: H103ESD

Revision Date: 10/31/2014

Page 1 of 7

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Wechem, Inc
5734 Susitna Dr
Harahan, LA 70123

Contact: Ligia M. Hernandez
Phone: 504-733-1152
Fax: 504-733-2218
Web: www.wechem.com

Product Name: Hulk System # 103ES
Revision Date: 10/31/2014
MSDS Number: H103ESD
Product Code: H103ES
Product Use: Industrial Cleaner / Degreaser

Emergency Telephone Number:
INFOTRAC
1-800-535-5053

2 HAZARDS IDENTIFICATION

Route of Entry: Skin absorption, ingestion, inhalation, eye
Target Organs: NA
Inhalation: Inhalation of generated mist can cause nasal and respiratory irritation or damage to respiratory tract.
Skin Contact: Causes irritation
Eye Contact: Causes irritation and burning
Ingestion: Harmful or fatal if swallowed.

PERSONAL PROTECTION INDEX											
A			G								
B			H								
C			I								
D			J								
E			K								
F			X	Consult your supervisor or S.O.P. for "SPECIAL" handling directions							
A		n		o		p		q		r	
t		u		w		y		z		Additional Information	

Hulk System # 103ES

MSDS Number: H103ESD

Revision Date: 10/31/2014

Page 2 of 7

GHS Signal Word:

WARNING

GHS Hazard Pictograms:



GHS Classifications:

Physical, Flammable Liquids, 4
Health, Acute toxicity, 5 Oral
Health, Skin corrosion/irritation, 2
Health, Serious Eye Damage/Eye Irritation, 2 B
Health, Specific target organ toxicity - Single exposure, 3

GHS Phrases:

H227 - Combustible liquid
H303 - May be harmful if swallowed
H315 - Causes skin irritation
H320 - Causes eye irritation
H335 - May cause respiratory irritation

GHS Precautionary Statements:

P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do.
Continue rinsing.

Hulk System # 103ES

MSDS Number: H103ESD

Revision Date: 10/31/2014

Page 3 of 7

3

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Chemical Name	Perc.	OSHA PEL (ppm)	ACGIH TLV(ppm)	Carcin. Ref.
NA	Glycol Surfactant Blend*	70-90%	NA	NA	D
102-71-6	Triethanolamine	3-7%	NA	5mg/m3	D
57-55-6	Propylene glycol	1-4%	NA	NA	D

*This product is a proprietary blend and chemical identity is withheld as a trade secret as per CFR 1910.1200

4

FIRST AID MEASURES

Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention.
Skin Contact:	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get immediate medical advice/attention.
Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get immediate medical advice/attention.
Ingestion:	If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

Hulk System # 103ES

MSDS Number: H103ESD

Revision Date: 10/31/2014

Page 4 of 7

5 FIRE FIGHTING MEASURES

Flammability: Combustible Liquid
Flash Point: 130 Deg. F.
Flash Point Method: PMCC
Burning Rate: ND
Autoignition Temp: ND
LEL: ND
UEL: ND

Extinguishing media: Foam, dry chemical, carbon dioxide, water

Special fire fighting procedures: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA)

Unusual Fire & Explosion Hazards: None

6 ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Avoid any contact with the skin and eyes.

Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Scoop up material and place in a disposal container. Provide ventilation.

7 HANDLING AND STORAGE

Handling Precautions: Combustible Liquid. Keep away from sources of ignition- No smoking. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Do not get in eyes, on skin, or on clothing. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.

Avoid freezing or excessive heat. Do not contaminate water, food or feed by storage or disposal

Laundry contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

Storage Requirements: Combustible Liquid. Keep out of reach of children. Keep container tightly closed and in a well-ventilated place. Store away from strong acids and oxidizers. Store in a cool dry, climate controlled area, away from incompatibles, sparks and open flame.

Hulk System # 103ES

MSDS Number: H103ESD

Revision Date: 10/31/2014

Page 5 of 7

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equip: HMIS PP, B | Goggles, Gloves
Respiratory Protection: None required under normal use conditions.
Protective gloves: Chemical resistant, rubber
Eye protection: Safety glasses/goggles

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear, dark green liquid	Odor:	Characteristic
Physical State:	Liquid	Molecular Formula:	NA
Particle Size:	NA	Solubility:	Complete
Spec Grav./Density:	(H2O=1): 0.95 +/- 0.05	Softening Point:	NA
Viscosity:	NA	Percent Volatile:	NA
Sat. Vap. Conc.:	NA	Heat Value:	NA
Boiling Point:	> 250 Deg. F.	Freezing/Melting Pt.:	NA
Vapor Pressure:	ND	Flash Point:	130 Deg. F.
pH:	9.5 +/- 0.5	Octanol:	NA
Evap. Rate:	NA	Vapor Density:	(Air=1): ND
Molecular weight:	NA	VOC:	NA
		Bulk Density:	NA

10

STABILITY AND REACTIVITY

Stability: Stable. No dangerous reaction known under conditions of normal use.

Conditions to Avoid: Heat. Incompatible materials.

Materials to Avoid: Strong oxidizers, acids

Hazardous Decomposition: Carbon dioxide, carbon monoxide

Hazardous Polymerization: Will not occur

Hulk System # 103ES

MSDS Number: H103ESD

Revision Date: 10/31/2014

Page 6 of 7

11

TOXICOLOGICAL INFORMATION

Data summary for the components are as follows:

Propylene Glycol (57-55-6)

Ingestion LD50 21,000 mg/kg (Rat)

Inhalation LC50 >105 ppm, 8 h (Rat)

Dermal LD50 20,800 mg/kg (Rat)

Surfactant Blend (Trade Secret)

Ingestion LD50 >1,400 mg/kg (Rat)

Triethanolamine (102-71-6)

Oral LD50 4190 mg/kg (Rat)

Dermal LD50 >2000 mg/kg (Rabbit)

12

ECOLOGICAL INFORMATION

Data summary for the components is as follows:

Propylene glycol (57-55-6)

Fish LC50 55,770 mg/l 96 h Fathead minnow (*Pimephales promelas*)

Daphnia EC50 >10,000 mg/l 48 h Daphnia

Surfactant Blend (Trade Secret)

Fish LC50 1-10 mg/l 96 h Fathead minnow (*Pimephales promelas*)

Daphnia EC50 1-10 mg/l 48h Daphnia magna

Algae EC50 1-10 mg/l 96h Algae

Triethanolamine (102-71-6)

Fish LC50 1800-11800 mg/l, 96h Fathead minnow (*Pimephales promelas*)

Daphnia LC50 739-2038 mg/l, 24h water flea (*Daphnia magna*)

Algae EC50 470-750 mg/l, 48h (alga *Scenedesmus* sp.) biomass growth inhibition

Micro-organisms EC50 >1000 mg/l, 3h activated sludge OECD 209

13

DISPOSAL CONSIDERATIONS

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Hulk System # 103ES

MSDS Number: H103ESD

Revision Date: 10/31/2014

Page 7 of 7

14

TRANSPORT INFORMATION

Proper Shipping Name: Not Regulated

15

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Glycol Surfactant Blend (CAS# Trade Secret 70-90%) TSCA

*Triethanolamine (102716 3-7%) HAP, MASS, PA, TSCA, TXAIR

*Propylene glycol (57556 1-4%) HAP, PA, TSCA

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

REGULATORY KEY DESCRIPTIONS

HAP = Hazardous Air Pollutants

MASS = MA Massachusetts Hazardous Substances List

OSHAWAC = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

SARA313 = SARA 313 Title III Toxic Chemicals

TXAIR = TX Air Contaminants with Health Effects Screening Level

TSCA = Toxic Substances Control Act

16

OTHER INFORMATION

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. ** Chemical listed as carcinogen or potential carcinogen. [a] NTP [b] IARC

Monograph [c] OSHA [d] Not listed [e] Animal Data only

N/A = Not available N/D = Not determined