

Hulk System FS 109 (Barrel in a Box)

SDS Number: HBFS109E

Revision Date: 3/13/2018

Page 1 of 9

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Wechem, Inc
5734 Susitna Dr
Harahan, LA 70123

Contact: Ligia M. Hernandez
Phone: 504-733-1152
Fax: 504-733-2218
Web: www.wechem.com

Product Identifier: Hulk System FS 109 (Barrel in a Box)
SDS Number: HBFS109E
Product Code: HBFS109
Revision Date: 3/13/2018
Product Use: Food Service Industrial Cleaner

Emergency Telephone Number:
INFOTRAC
1-800-535-5053

2

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Acute toxicity, 4 Oral
Health, Skin corrosion/irritation, 1 B
Health, Specific target organ toxicity - Single exposure, 3
Health, Specific target organ toxicity - Single exposure, 2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H335 - May cause respiratory irritation
H371 - May cause damage to organs

GHS Precautionary Statements:

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Skin absorption, ingestion, inhalation, eye

Hulk System FS 109 (Barrel in a Box)

SDS Number: HBFS109E

Revision Date: 3/13/2018

Page 2 of 9

Target Organs: NA
Inhalation: Inhalation of generated mist can cause nasal and respiratory irritation or damage to respiratory tract.
Skin Contact: Causes irritation
Eye Contact: Causes irritation and burning
Ingestion: Harmful or fatal if swallowed.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
111-76-2	>30%	Glycol Surfactant Mixture*
141-43-5	15-40%	Ethanol, 2-amino-
57-55-6	1-4%	Propylene glycol

* Ethylene glycol monobutyl ether

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention.
Skin Contact: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get immediate medical advice/attention.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get immediate medical advice/attention.
Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

5 FIRE FIGHTING MEASURES

Flammability: NA
Flash Point: No flash below 200 Deg. F.
Flash Point Method: PMCC
Burning Rate: ND
Autoignition Temp: ND
LEL: ND
UEL: ND

Extinguishing media: Foam, dry chemical, carbon dioxide, water

Special fire fighting procedures: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA)

Unusual Fire & Explosion Hazards: None

6 ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Avoid any contact with the skin and eyes.

Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Scoop up material and place in a disposal container. Provide ventilation.

7 HANDLING AND STORAGE

Hulk System FS 109 (Barrel in a Box)

SDS Number: HBFS109E

Revision Date: 3/13/2018

Page 3 of 9

Handling Precautions: Corrosive liquid. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Do not get in eyes, on skin, or on clothing. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practices.

Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

Storage Requirements: Corrosive liquid. Handle all containers carefully. Keep out of reach of children.
Keep container tightly closed and in a well-ventilated place. Store locked up.

8	EXPOSURE CONTROLS/PERSONAL PROTECTION
----------	--

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment: HMIS PP, B | Goggles, Gloves
Respiratory Protection: None required under normal use conditions.
Protective gloves: Chemical resistant, rubber
Eye protection: Safety glasses/goggles

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

Ethylene glycol monobutyl ether cas#:(111-76-2) [>30%]

Components with workplace control parameters

TWA 20 ppm USA. ACGIH Threshold Limit Values (TLV)

Eye & Upper Respiratory Tract irritation
Confirmed animal carcinogen with unknown relevance to humans

TWA 5 ppm USA. NIOSH Recommended Exposure Limits
24 mg/m3

Potential for dermal absorption

TWA 50 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
240 mg/m3

Skin designation
The value in mg/m3 is approximate.

TWA 25 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
120 mg/m3

Skin notation

Ethanol, 2-amino- cas#:(141-43-5) [15-40%]

Components with workplace control parameters

TWA 3 ppm USA. ACGIH Threshold Limit Values (TLV)

Skin & eye irritation

STEL 6 ppm USA. ACGIH Threshold Limit Values (TLV)

SDS Number: HBFS109E Hulk System FS 109 (Barrel in a Box)

Revision Date: 3/13/2018

Page 4 of 9

Skin & eye irritation

TWA	3 ppm 8 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
-----	------------------------------	--

STEL	6 ppm 15 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
------	-------------------------------	--

TWA	3 ppm 6 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
-----	------------------------------	--

 The value in mg/m³ is approximate.

TWA	3 ppm 8 mg/m ³	USA. NIOSH Recommended Exposure Limits
-----	------------------------------	---

ST	6 ppm 15 mg/m ³	USA. NIOSH Recommended Exposure Limits
----	-------------------------------	---

Propylene glycol cas#:(57-55-6) [1-4%]

Components with workplace control parameters

TWA	10 mg/m ³	USA. Workplace Environmental Exposure Levels (WEEL)
-----	----------------------	--

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Dark blue liquid	Odor:	Characteristic
Physical State:	Liquid	Molecular Formula:	NA
Particle Size:	NA	Solubility:	Complete
Spec Grav./Density:	(H ₂ O=1): 0.97 +/- 0.1	Softening Point:	NA
Viscosity:	NA	Percent Volatile:	NA
Saturated Vapor Concentration:	NA	Heat Value:	NA
Boiling Point:	NA	Freezing/Melting Pt.:	NA
Vapor Pressure:	ND	Flash Point:	No flash below 200 Deg. F.
pH:	> 12	Octanol:	NA
Evap. Rate:	NA	Vapor Density:	(Air=1): ND
Molecular weight:	NA	VOC:	~ 74 %
		Bulk Density:	NA

10

STABILITY AND REACTIVITY

Chemical Stability:	Stable. No dangerous reaction known under conditions of normal use.
Conditions to Avoid:	Incompatible materials.
Materials to Avoid:	Strong oxidizers, acids
Hazardous Decomposition:	Carbon dioxide, carbon monoxide
Hazardous Polymerization:	Will not occur

Hulk System FS 109 (Barrel in a Box)

SDS Number: HBFS109E

Revision Date: 3/13/2018

Page 5 of 9

11

TOXICOLOGICAL INFORMATION

Data summary for the components are as follows:

Surfactant Blend (Trade Secret)
Ingestion LD50 >1,400 mg/kg (Rat)

Ethylene glycol monobutyl ether cas#:(111-76-2) [>30%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 470 mg/kg

LC50 Inhalation - rat - 4 h - 450 ppm Remarks: Behavioral:Ataxia. Nutritional and Gross Metabolic:Weight loss or decreased weight gain.

LD50 Dermal - rabbit - 220 mg/kg

LD50 Intraperitoneal - rat - 220 mg/kg

LD50 Intravenous - rat - 307 mg/kg

Skin corrosion/irritation: Skin - rabbit Result: Open irritation test

Serious eye damage/eye irritation: Eyes - rabbit Result: Moderate eye irritation - 24 h

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Butoxyethanol)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Overexposure may cause reproductive disorder(s) based on tests with laboratory animals.

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: KJ8575000

Ethanol, 2-amino- cas#:(141-43-5) [15-40%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 1,720 mg/kg

Inhalation: Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract.

LD50 Dermal - rabbit - 1,015 mg/kg

no data available

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: Eyes - rabbit Result: Severe eye irritation

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human

Hulk System FS 109 (Barrel in a Box)

SDS Number: HBFS109E

Revision Date: 3/13/2018

Page 6 of 9

carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: KJ5775000

Propylene glycol cas#:(57-55-6) [1-4%]

Information on toxicological effects

Acute toxicity:

Oral LD50 LD50 Oral - rat - 20,000 mg/kg

Inhalation LC50 no data available

Dermal LD50 LD50 Dermal - rabbit - 20,800 mg/kg

Other information on acute toxicity LD50 Intramuscular - rat - 14 g/kg

LD50 Intravenous - dog - 26 g/kg

LD50 Intraperitoneal - rat - 6,660 mg/kg

LD50 Subcutaneous - rat - 22,500 mg/kg

LD50 Intravenous - rat - 6,423 mg/kg

LD50 Intraperitoneal - mouse - 9,718 mg/kg

Remarks: Lungs, Thorax, or Respiration:Chronic pulmonary edema. Kidney, Ureter, Bladder:Changes in both tubules and glomeruli. Blood:Changes in spleen.

LD50 Subcutaneous - mouse - 17,370 mg/kg

Remarks: Behavioral:Change in motor activity (specific assay). Behavioral:Muscle contraction or spasticity. Cyanosis

LD50 Intravenous - mouse - 6,630 mg/kg

LD50 Intravenous - rabbit - 6,500 mg/kg

Skin corrosion/irritation: Skin - Human - Mild skin irritation - 7 d

Serious eye damage/eye irritation: Eyes - rabbit - Mild eye irritation

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):
no data availableSpecific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available

Aspiration hazard: no data available

Hulk System FS 109 (Barrel in a Box)

SDS Number: HBFS109E

Revision Date: 3/13/2018

Page 7 of 9

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Gastrointestinal disturbance, Nausea, Headache, Vomiting, Central nervous system depression

Synergistic effects: no data available

Additional Information:

RTECS: TY2000000

12

ECOLOGICAL INFORMATION

Data summary for the components is as follows:

Surfactant Blend (Trade Secret)

Fish LC50 1-10 mg/l 96 h Fathead minnow (*Pimephales promelas*)

Daphnia EC50 1-10 mg/l 48h Daphnia magna

Algae EC50 1-10 mg/l 96h Algae

Ethylene glycol monobutyl ether cas#:(111-76-2) [>30%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - other fish - 220 mg/l - 96 h.

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 1,815 mg/l - 24 h.

other aquatic invertebrates

Persistence and degradability: no data available

Ratio BOD/ThBOD 88 %

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

Ethanol, 2-amino- cas#:(141-43-5) [15-40%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - *Pimephales promelas* (fathead minnow) - 227 mg/l - 96 h.

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 65 mg/l - 48 h.

other aquatic invertebrates

Toxicity to algae EC50 - *Desmodesmus subspicatus* (green algae) - 15 mg/l - 72 h.

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Hulk System FS 109 (Barrel in a Box)

SDS Number: HBFS109E

Revision Date: 3/13/2018

Page 8 of 9

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

Propylene glycol cas#:(57-55-6) [1-4%]

Information on ecological effects

Toxicity:

Toxicity to fish mortality NOEC - Pimephales promelas (fathead minnow) - 52,930 mg/l - 96 h.

Toxicity to daphnia mortality NOEC - Daphnia - 13,020 mg/l - 48 h.

and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - > 10,000 mg/l - 48 h

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

13	DISPOSAL CONSIDERATIONS
-----------	--------------------------------

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

14	TRANSPORT INFORMATION
-----------	------------------------------

Proper Shipping Name: UN 1760, Corrosive Liquids, N.O.S., (Ethanalamine), 8, PG III

15	REGULATORY INFORMATION
-----------	-------------------------------

Component (CAS#) [%] - CODES

 Ethylene glycol monobutyl ether (111-76-2) [>30%] HAP, MASS, OSHAWAC, PA, SARA313, TSCA, TXAIR

Ethanol, 2-amino- (141-43-5) [15-40%] HAP, MASS, OSHAWAC, PA, TSCA, TXAIR

Propylene glycol (57-55-6) [1-4%] HAP, PA, TSCA

This product is NOT for sale in CA, UT, OTC or LADCO States.

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory CODE Descriptions

 HAP = Hazardous Air Pollutants

MASS = MA Massachusetts Hazardous Substances List

OSHAWAC = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

SARA313 = SARA 313 Title III Toxic Chemicals

TSCA = Toxic Substances Control Act

TXAIR = TX Air Contaminants with Health Effects Screening Level

Hulk System FS 109 (Barrel in a Box)

SDS Number: HBFS109E

Revision Date: 3/13/2018

Page 9 of 9

16

OTHER INFORMATION

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

N/A = Not available N/D = Not determined

Revision Date: 3/13/2018