

Infinity (Aerosol) (Rev 11-12-24)

SDS Number: A135C

Revision Date: 11/12/2024

Page 1 of 13

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Wechem, Inc
5734 Susitna Dr
Harahan, LA 70123

Contact: Ligia M. Hernandez
Phone: 504-733-1152
Fax: 504-733-2218
Web: www.wechem.com

Product Identifier: Infinity (Aerosol) (Rev 11-12-24)
SDS Number: A135C
Product Code: A135
Revision Date: 11/12/2024
Product Use: Penetrating Oil

Emergency Telephone Number:
INFOTRAC
1-800-535-5053

2

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Aerosols, 1
Health, Aspiration hazard, 2
Health, Skin corrosion/irritation, 2
Health, Serious Eye Damage/Eye Irritation, 2 A
Health, Specific target organ toxicity - Single exposure, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Hazard Statements:

H222 - Extremely flammable aerosol
H229 - Pressurized container: may burst if heated
H305 - May be harmful if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

GHS Precautionary Statements:

P102 - Keep out of reach of children.
P103 - Read label before use.
P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing gas/mist/vapours/spray.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Infinity (Aerosol) (Rev 11-12-24)

SDS Number: A135C

Revision Date: 11/12/2024

Page 2 of 13

P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352 - If on skin: Wash with plenty of soap and water.
P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 - IF exposed or concerned: Get medical advice/ attention.
P312 - Call a POISON CENTER/doctor if you feel unwell.
P321 - Specific treatment (see ... on this label).
P331 - Do NOT induce vomiting.
P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313 - If eye irritation persists: Get medical advice/attention.
P362 + P364 - Take off contaminated clothing and wash it before reuse.
P403 - Store in a well-ventilated place.
P405 - Store locked up.
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Inhalation, ingestion, skin absorption, eyes
Target Organs: NA
Inhalation: High vapor/aerosol concentrations are irritating to the eyes and respiratory tract.
Skin Contact: May cause skin irritation.
Eye Contact: May cause serious eye irritation.
Ingestion: Harmful if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

3

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
64742-47-8	15-40%	Distillates, petroleum, hydrotreated light
64742-46-7	15-40%	Distillates, petroleum, hydrotreated middle
74-98-6	10-20%	Propane
106-97-8	5-10%	Butane
34590-94-8	5-10%	Dipropylene glycol methyl ether
64742-95-6	5-10%	Solvent naphtha, petroleum, light arom.
78-92-2	1-5%	sec-Butyl alcohol
8002-09-3	<10%	Pine oil
123-42-2	<5%	Diacetone alcohol

4

FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention.
Skin Contact: Immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical advice/attention.
Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get immediate medical advice/attention.
Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

DANGER. Extremely flammable. Contents under pressure. Harmful if swallowed. Aspiration hazard if swallowed. Vapor harmful. Keep away from heat and flame. Can cause nervous system depression.

5

FIRE FIGHTING MEASURES

Flammability: Extremely Flammable Aerosol

Infinity (Aerosol) (Rev 11-12-24)

SDS Number: A135C

Revision Date: 11/12/2024

Page 3 of 13

Flash Point: 115 Deg. F (Liquid portion)
Flash Point Method: PMCC
Burning Rate: Not determined
Autoignition Temp: Not determined
LEL: Not determined
UEL: Not determined
 Suitable fire extinguishing media: Use water spray, fog or foam.

Specific hazards arising from the chemical: Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products: Carbon Dioxide, Carbon Monoxide

Specific fire-fighting methods: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire fighters: Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

6

ACCIDENTAL RELEASE MEASURES

Personal precautions:

Put on appropriate personal protective equipment (see section 8)

Environmental precautions and clean-up methods:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

7

HANDLING AND STORAGE

Handling Precautions:

Pressurized container: Do not pierce or burn, even after use. Do not use or store near heat, sparks or open flame. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Storage Requirements:

Level 3 Aerosol.

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

Ventilation Requirement: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Infinity (Aerosol) (Rev 11-12-24)

SDS Number: A135C

Revision Date: 11/12/2024

Page 4 of 13

Personal Protective Equipment:

Eye/face protection: Face shield is recommended. Wear safety glasses with side shields (or goggles).
 Hand protection : Wear appropriate chemical resistant gloves.
 Skin protection (Other): Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
 Respiratory protection: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.'

Propane cas#:(74-98-6) [10-20%]

Components with workplace control parameters

TWA	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)
-----	-----------	---

Central Nervous System impairment
Cardiac sensitization

TWA	1,000 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	1,800 mg/m3	

The value in mg/m3 is approximate.

TWA	1,000 ppm	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
	1,800 mg/m3	

TWA	1,000 ppm	USA. NIOSH Recommended Exposure Limits
	1,800 mg/m3	

Butane cas#:(106-97-8) [5-10%]

Components with workplace control parameters

TWA	800 ppm	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
	1,900 mg/m3	

TWA	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)
-----	-----------	---

TWA	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)
-----	-----------	---

Central Nervous System impairment Cardiac sensitization

TWA	800 ppm	USA. NIOSH Recommended Exposure Limits
	1,900 mg/m3	

Also see specific listing for Isobutane.

Dipropylene glycol methyl ether cas#:(34590-94-8) [5-10%]

Components with workplace control parameters

TWA	100 ppm	USA. ACGIH Threshold Limit Values (TLV)
-----	---------	---

Eye & Upper Respiratory Tract irritation Central Nervous System impairment Danger of cutaneous

Infinity (Aerosol) (Rev 11-12-24)

SDS Number: A135C

Revision Date: 11/12/2024

Page 5 of 13

absorption

STEL 150 ppm USA. ACGIH Threshold Limit Values (TLV)
Eye & Upper Respiratory Tract irritation Central Nervous System impairment Danger of cutaneous absorption

TWA 100 ppm USA. Occupational Exposure Limits (OSHA) - Table Z- 1
600 mg/m3 Limits for Air Contaminants

Skin designation The value in mg/m3 is approximate.

TWA 100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
600 mg/m3 1910.1000

Skin notation

STEL 150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
900 mg/m3 1910.1000

Skin notation

TWA 100 ppm USA. NIOSH Recommended Exposure Limits
600 mg/m3

Potential for dermal absorption

ST 150 ppm USA. NIOSH Recommended Exposure Limits
900 mg/m3

Potential for dermal absorption

sec-Butyl alcohol cas#:(78-92-2) [1-5%]

Components with workplace control parameters

TWA 100 ppm USA. ACGIH Threshold Limit Values (TLV)
Central Nervous System impairment Upper Respiratory Tract irritation

TWA 150 ppm USA. Occupational Exposure Limits (OSHA) - Table Z- 1
450 mg/m3 Limits for Air Contaminants

The value in mg/m3 is approximate.

TWA 100 ppm USA. NIOSH Recommended Exposure Limits
305 mg/m3

ST 150 ppm USA. NIOSH Recommended Exposure Limits
455 mg/m3

Diacetone alcohol cas#:(123-42-2) [<5%]

Components with workplace control parameters

TWA 50 ppm USA. ACGIH Threshold Limit Values (TLV)
Eye & Upper Respiratory Tract irritation

TWA 50 ppm USA. NIOSH Recommended Exposure Limits
240 mg/m3

TWA 50 ppm USA. Occupational Exposure Limits (OSHA) - Table Z- 1
240 mg/m3 Limits for Air Contaminants

Infinity (Aerosol) (Rev 11-12-24)

SDS Number: A135C

Revision Date: 11/12/2024

Page 6 of 13

The value in mg/m3 is approximate.

TWA	50 ppm	USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
	240 mg/m3	1910.1000

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Reddish orange aerosol	Odor:	Terpene
Physical State:	Liquid	Solubility:	Insoluble
Spec Grav./Density:	0.84 +/- 0.05	Percent Volatile:	85-95%
Vapor Pressure:	40-82 Psi	Flash Point:	115 Deg. F (Liquid Portion)
		VOC:	42.2% Wt.

10

STABILITY AND REACTIVITY

Reactivity:	Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical Stability:	Stable and non-reactive under normal conditions of use, storage and transport.
Conditions to Avoid:	High temperatures, open flames, sparks, welding. Vapors may ignite at temperatures exceeding flash point.
Materials to Avoid:	Acids and strong oxidizers
Hazardous Decomposition:	Carbon dioxide, carbon monoxide
Hazardous Polymerization:	Will not occur

11

TOXICOLOGICAL INFORMATION

Primary Route of Entry: Skin contact, inhalation

Acute/Potential Health Effects:

EYES: May cause serious eye irritation. Symptoms include stinging, tearing and redness.

SKIN: May cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying of skin and skin burns.

INHALATION: High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects. May cause peripheral nervous system disorder and/or damage.

INGESTION: Harmful if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

Chronic / Long Term Effects: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Signs and Symptoms of Overexposure: Signs and symptoms of overexposure to this material through breathing, swallowing, and/or passage of material through the skin may include: stomach or intestinal upset (nausea vomiting, diarrhea) irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

Target Organ Effects: Central nervous system.

Reproductive/Developmental Information: None known

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

Acute Toxicity Values:

Not available.

Propane cas#:(74-98-6) [10-20%]

Information on toxicological effects

Infinity (Aerosol) (Rev 11-12-24)

SDS Number: A135C

Revision Date: 11/12/2024

Page 7 of 13

Acute toxicity: no data available

Inhalation: no data available

Dermal: no data available

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: TX2275000

Dizziness, Drowsiness, Unconsciousness

Butane cas#:(106-97-8) [5-10%]

Information on toxicological effects**Acute toxicity:**

Oral LD50 no data available

Inhalation LC50 LC50 Inhalation - rat - 4 h - 658,000 mg/m3

Dermal LD50

Other information on acute toxicity

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Infinity (Aerosol) (Rev 11-12-24)

SDS Number: A135C

Revision Date: 11/12/2024

Page 8 of 13

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):
no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation.

Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Central nervous system depression, giddiness, Shortness of breath, narcosis, Dermal contact with rapidly evaporating liquid could result in freezing of the tissues or frostbite., Exposure can cause numbness, tingling, and weakness in extremities., Cyanosis, Pulmonary edema. Effects may be delayed., Abdominal pain, Nausea, Vomiting

Synergistic effects: no data available

Additional Information:

RTECS: EJ4200000

Dipropylene glycol methyl ether cas#:(34590-94-8) [5-10%]

Information on toxicological effects

Acute toxicity:

Oral LD50 LD50 Oral - rat - 5,152 mg/kg

Inhalation LC50 no data available

Dermal LD50

Other information on acute toxicity

Skin corrosion/irritation: Serious eye damage/eye irritation:

Eyes - rabbit - Mild eye irritation - 24 h

Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Infinity (Aerosol) (Rev 11-12-24)

SDS Number: A135C

Revision Date: 11/12/2024

Page 9 of 13

Specific target organ toxicity - single exposure (Globally Harmonized System):
no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed.

Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information:

RTECS: JM1575000

sec-Butyl alcohol cas#:(78-92-2) [1-5%]

Information on toxicological effects

Acute toxicity:

Oral LD50 LD50 Oral - rat - 2,193 mg/kg Remarks: Behavioral:Somnolence (general depressed activity). Behavioral:Ataxia. Behavioral:Coma.

Inhalation LC50 Dermal LD50 Dermal - rat - > 2,000 mg/kg

Other information on acute toxicity no data available

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: Reproductive toxicity - rat - Inhalation:

Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants). Effects on Embryo or Fetus: Fetal death. Specific Developmental Abnormalities: Musculoskeletal system.
no data available

Teratogenicity: Developmental Toxicity - rat - Inhalation:

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).
no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):
May cause respiratory irritation. May cause drowsiness or dizziness.

Infinity (Aerosol) (Rev 11-12-24)

SDS Number: A135C

Revision Date: 11/12/2024

Page 10 of 13

Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available

Aspiration hazard: no data available

Signs and Symptoms of Exposure: Nausea, Dizziness, Headache, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information:

RTECS: EO1750000

Diacetone alcohol cas#:(123-42-2) [<5%]

Information on toxicological effects

Acute toxicity:

Oral LD50 LD50 Oral - rat - 2,520 mg/kg Remarks: Behavioral:Tremor. Behavioral:Convulsions or effect on seizure threshold. Liver:Other changes.

Inhalation LC50 LC50 Inhalation - rat - 4 h - 1500 ppm

Dermal LD50 LD50 Dermal - rabbit - 13,500 mg/kg

Other information on acute toxicity no data available

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: Eyes - rabbit - Severe eye irritation - 24 h

Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):
no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.

Signs and Symptoms of Exposure: Central nervous system depression, Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness., Blood disorders, Dermatitis, Blurred vision, Effects due to ingestion may include:, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Infinity (Aerosol) (Rev 11-12-24)

SDS Number: A135C

Revision Date: 11/12/2024

Page 11 of 13

Synergistic effects: no data available

Additional Information:

RTECS: SA9100000

12

ECOLOGICAL INFORMATION

Propane cas#:(74-98-6) [10-20%]

Information on ecological effects

Toxicity: no data available

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

Butane cas#:(106-97-8) [5-10%]

Information on ecological effects

Toxicity: no data available

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

Dipropylene glycol methyl ether cas#:(34590-94-8) [5-10%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - > 10,000 mg/l - 96 h.

Toxicity to daphnia EC50 - Daphnia magna (Water flea) - 1,919 mg/l - 48 h.

and other aquatic invertebrates

Persistence and degradability: Biodegradability

Bioaccumulative potential: no data available

Mobility in soil: no data available

Infinity (Aerosol) (Rev 11-12-24)

SDS Number: A135C

Revision Date: 11/12/2024

Page 12 of 13

PBT and vPvB assessment: no data available

Other adverse effects: no data available

sec-Butyl alcohol cas#:(78-92-2) [1-5%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 3,670 mg/l - 96 h.

Toxicity to daphnia EC50 - Daphnia magna (Water flea) - 4,227 mg/l - 48 h.

and other aquatic invertebrates

EC100 - Daphnia magna (Water flea) - 5,000 mg/l - 24 h

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

Diacetone alcohol cas#:(123-42-2) [<5%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Lepomis macrochirus (Bluegill) - 420 mg/l - 96 h.

Toxicity to daphnia EC50 - Daphnia magna (Water flea) - 9,000 mg/l - 24 h.

and other aquatic invertebrates

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

13

DISPOSAL CONSIDERATIONS

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may

Infinity (Aerosol) (Rev 11-12-24)

SDS Number: A135C

Revision Date: 11/12/2024

Page 13 of 13

retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14

TRANSPORT INFORMATION
UN number 1950

Proper shipping name Aerosols, flammable

Class 2.1

Packing group -

15

REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[15-40%] Distillates, petroleum, hydrotreated light (64742-47-8) TSCA

[15-40%] Distillates, petroleum, hydrotreated middle (64742-46-7) TSCA

[10-20%] Propane (74-98-6) MASS, NJHS, OSHAWAC, PA, TSCA, TXAIR

[5-10%] Butane (106-97-8) MASS, NJHS, OSHAWAC, PA, TSCA, TXAIR

[5-10%] Dipropylene glycol methyl ether (34590-94-8) MASS, OSHAWAC, PA, TSCA, TXAIR

[5-10%] Solvent naphtha, petroleum, light arom. (64742-95-6) TSCA

[1-5%] sec-Butyl alcohol (78-92-2) MASS, NJHS, OSHAWAC, PA, SARA313, TSCA, TXAIR

[<10%] Pine oil (8002-09-3) TSCA

[<5%] Diacetone alcohol (123-42-2) MASS, OSHAWAC, PA, TSCA, TXAIR

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory Code Legend

TSCA = Toxic Substances Control Act

MASS = MA Massachusetts Hazardous Substances List

NJHS = NJ Right-to-Know Hazardous Substances

OSHAWAC = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TXAIR = TX Air Contaminants with Health Effects Screening Level

SARA313 = SARA 313 Title III Toxic Chemicals

16

OTHER INFORMATION

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

N/A = Not available N/D = Not determined

Revision Date: 11/12/2024