PROTECTO FLEX is a long term, flexible, weldable, metal parts protector. When applied, it will prevent rust and corrosion on all metal parts. Affords long term protection for indoor or outdoor storage. Excellent for protecting materials while in transit. This product is USDA authorized. A 2 or 3 mil coating will provide indefinite protection for indoor storage and 6 months to 1 year protection for outdoor storage. A 5 or 6 mil coating will protect materials for up to 2 years in outdoor storage. Film is a transparent amber, easy to see through. Can be removed by washing with kerosene or mineral spirits. Once removed, parts can be painted.

## **FOR USE ON:**

All exposed metal parts, bearing, cables, chains, housings, jigs, precision machined surfaces, stampings, large molds, offshore drilling parts, outdoor airport ground handling equipment, castings, metal parts in ground or ocean transit, seasonal equipment in storage and any metal part needing to be temporarily sealed against corrosion.

## **DIRECTIONS:**

- 1. Make sure surface is clean and free of rust, scale or dirt
- 2. Remove protective cap. Point opening in spray tip towards part to be coated.
- 3. Holding can 8 to 10 inches from part, spray 2 or 3 mil coat with a slow sweeping motion. Completely wet surface. (For extremely severe conditions, wait 5 minutes and apply another coat)
- 4. Product will completely set up in 2 hours. Once the film is hard, part can be handled. Dust and dirt can be wiped off without affecting film.

WECHEM, INC. 5734 Susitna Dr. • Harahan, LA 70123 504.733.1152 • 1.800.426.0512 FAX 504.733.2218 • www.wechem.com







## DANGER:

Extremely flammable aerosol. Contains gas under pressure: may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eve irritation. May cause drowsiness or dizziness. May cause cancer. May cause genetic defects. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid breathing dust/fume/gas/mist/vapors/spray, Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves and eve protection. Store locked up in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local/regional/national/international regulations.

IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

**IF IN EYES**: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**IF SWALLOWED:** Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.

MARNING: This product can expose you to chemicaals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

CONTAINS (CAS): Propane/ n-Butane (68476-86-8), Naphtha, petroleum, hydrotreated heavy (64742-48-9), Heptane (142-82-5)

See Safety Data Sheet for complete safety information. 24 HOUR MEDICAL EMERGENCY 1-800-535-5053 CONTAINS NO OZONE DEPLETING CHEMICALS!

## SCAN FOR SDS





MADE IN THE USA