

QC LUBE is a one-step cleaner and lubricant that penetrates to coat contacts and provides corrosion protection on switchgear blade mechanisms. **QC LUBE** includes High Purity Solvents for cleaning and a special grade silicone for lubricating. Removes grease, dirt, oil, and operating erosion from all electro-mechanical devices. Safe for use on metering, distribution, and substation class switchgear contacts. **QC LUBE** protects against atmospheric contaminant buildup that can cause sticking blades or contacts, and does not degrade seals, gaskets, and most plastic insulators making it safe for use on most rubber and plastics.

QC LUBE, a multi-purpose silicone spray that forms an oxygen barrier and helps reduce corona cutting and weather checking on rubber equipment. **QC LUBE** also reduces surface creepage due to wet weather and high humidity.

DIRECTIONS

Thoroughly clean the surface to be sprayed with **QC LUBE**. Spray a light film with a sweeping motion. When used on sticking surfaces, work object back and forth. Spray again if necessary.

This solvent system has tested safe on: Neoprene, Buna, Silicone, Butyl and Natural Rubber, Nylon, Hypalon®, PTFE, PVC, Polyurethane, Polyethylene, Polypropylene and Epoxy.

NOTE: Product may harm some plastics. TEST ALL SURFACES IF NOT LISTED ON LABEL BEFORE USE.

Rev. 10.2023



Engineered Chemistries
SUPERIOR SOLUTIONS

QC LUBE™

High Voltage Switchgear Cleaner & Lubricant

**CLEANS, PENETRATES & LUBRICATES
PREVENTS CORROSION
USE ON STATIONARY CONTACTS & TERMINALS
30,000 VOLT DIELECTRIC STRENGTH
PER (ASTM D877)*
NON-FLAMMABLE, DRIES FAST, ZERO RESIDUE**

DANGER

**CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON SIDE PANEL.**

Net Wt. 11 OZ / 312 g



DANGER

Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Dispose of contents/container in accordance with local/regional/national/international regulations. Wear protective gloves and eye protection. Wash hands thoroughly after handling. Avoid breathing mist, vapors or spray. Do not eat drink or smoke when using this product.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

IF ON SKIN: Immediately wash with water for 15 minutes. Get medical attention if irritation develops and persists.

IF IN EYES: Rinse with water. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

IF SWALLOWED: Rinse mouth. Do not induce vomiting. Keep head below hips if vomiting occurs. Get medical attention immediately.

Contains: Trans-1,2-Dichloroethylene (156-60-5), 1,1,2,2-Tetrafluoroethyl-2,2,2-trifluoroethylether (406-78-0), Carbon dioxide (124-38-9)

KEEP OUT OF REACH OF CHILDREN.


See Safety Data Sheet for complete safety information.

24 HOUR MEDICAL EMERGENCY: 1-800-535-5053.

CONTAINS NO OZONE DEPLETING CHEMICALS!



SCAN FOR SDS



Wechem, Inc.

5734 Susitna Dr • Harahan, LA 70123

(504) 733-1152 • 800-426-0512

FAX (504) 733-2218 • WWW.WECHEM.COM