

**HIGH SOLIDS • HIGH TEMPERATURE  
HIGH STRENGTH FAST TACK**

**STICK IT** is a high performance aerosol adhesive offering rapid setting and quick dry time. Formulated to totally dry clear within 15 minutes. Ideal for use on uneven or porous surfaces. Suitable where high temperature may be encountered as well as uses where a clear, flexible, non-wrinkling, waterproof bond is desired. VOC compliant\*.

#### USE ON:

**Porous & Uneven Surfaces  
Cardboard • Leather • Wood  
Most Plastics • Paper • Glass  
Carpet Backings • Fabrics**

#### DIRECTIONS

##### SHAKE WELL BEFORE USING.

Bonding surfaces must be free from dust and debris. For best results, use at temperatures above 50°F (10°C). Spray from a distance of 8-10 inches, keeping the tip moving in order to get an even webbing of adhesive on the surface to be bonded. If a permanent bond is desired, spray both surfaces, allow adhesive to dry to a tack and then bond.

#### CLEANING SPRAY TIP

When finished with application, always turn can upside down and spray for two seconds to clear valve and prevent clogging. If adhesive accumulates around nozzle, wipe clear while wet. If dried in valve opening, remove with degreasing solvent. Not recommended for unsupported vinyl fabric. Certain plastic and elastomeric substrates can exhibit bond failure due to plasticizer migration. Combinations of high temperature and humidity can promote bond failure. Testing of production parts in typical operating environments for compatibility is recommended. Excess adhesive or over-spray can be cleaned up with a petroleum solvent.



Engineered Chemistries  
**SUPERIOR SOLUTIONS**

# STICK IT™

## Heavy-Duty Adhesive Spray

- \*WIDE WEB SPRAY PATTERN
- \*HIGH SOLIDS
- \*WATER - RESISTANT
- \*NO CHLORINATED SOLVENTS

sample

**DANGER: EXTREMELY FLAMMABLE.  
VAPOR HARMFUL. HARMFUL OR FATAL IF  
SWALLOWED. CONTENTS UNDER PRESSURE.**

**KEEP OUT OF REACH OF CHILDREN.**

**READ CAUTIONS ON RIGHT SIDE PANEL.**

SI USTED NO ENTIENDE LA ETIQUETA, BUSQUE A ALGUIEN PARA  
QUE SE LA EXPLIQUE A USTED EN DETALLE. (If you do  
not understand this label, find someone to explain it to you in detail.)

**NET WT. 12 OZ (340 GRAMS)**



**DANGER:** Keep out of reach of children. Read label and sds before use. Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. May cause damage to central nervous system through prolonged or repeated exposure via inhalation. Suspected of damaging fertility or the unborn child. Causes skin irritation. Causes serious eye irritation.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/spray. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks, open flames and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands and face thoroughly after handling. Wear protective gloves. Wear eye protection. If exposed or concerned: Get medical attention.

**FIRST AID: IF SWALLOWED:** Immediately call a poison center or a doctor. Do NOT induce vomiting. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation occurs get medical attention. Take off contaminated clothing and wash it before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, and national regulations.

**INGREDIENTS (C.A.S.#):** Acetone (67-64-1), Hexane (110-54-3), Propane (74-98-6), Butane (106-97-8).

**HMIS RATINGS:** Health: 2; Flammability: 4; Reactivity: 0; Maximum Personal Protection: G

VOC Category: Web Spray Adhesive.

\*Meets the VOC Standard of 55% by weight.

**\*NOT FOR SALE IN CALIFORNIA.**

This product is designed exclusively for industrial and institutional use by trained personnel. This product is sold "as is" and the manufacturer makes no warranty, express or implied, of merchantability, fitness for a particular purpose or otherwise.

07.2023

46222015788.071323



SCAN FOR SDS



To Reorder:  
WECHEM, INC.  
5734 Susitna Dr.  
Harahan, LA 70123  
504.733.1152  
800.426.0512  
FAX 504.733.2218  
www.wechem.com

