

Stick It

SDS Number: A215A

Revision Date: 6/30/2023

Page 1 of 13

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Wechem, Inc
 5734 Susitna Dr
 Harahan, LA 70123

Contact: Ligia M. Hernandez
Phone: 504-733-1152
Fax: 504-733-2218
Web: www.wechem.com

Product Identifier: Stick It
SDS Number: A215A
Product Code: A215
Revision Date: 6/30/2023
Product Use: Heavy Duty Adhesive Spray

Emergency Telephone Number:
 INFOTRAC
 1-800-535-5053

2

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Aerosols, 1
 Physical, Gases Under Pressure, Liquefied Gas
 Health, Aspiration hazard, 1
 Health, Skin corrosion/irritation, 2
 Health, Serious Eye Damage/Eye Irritation, 2 A
 Health, Specific target organ toxicity - Single exposure, 3
 Health, Reproductive toxicity, 2
 Health, Specific target organ toxicity - Repeated exposure, 2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

H222 - Extremely flammable aerosol
 H280 - Contains gas under pressure; may explode if heated
 H304 - May be fatal if swallowed and enters airways
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H336 - May cause drowsiness or dizziness
 H361 - Suspected of damaging fertility or the unborn child
 H373 - May cause damage to central nervous system through prolonged or repeated exposure via inhalation.

GHS Precautionary Statements:

P102 - Keep out of reach of children.
 P103 - Read label and SDS before use.
 P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

Stick It

SDS Number: A215A

Revision Date: 6/30/2023

Page 2 of 13

P211 - Do not spray on an open flame or other ignition source.
 P251 - Pressurized container: Do not pierce or burn, even after use.
 P260 - Do not breathe mist or vapor.
 P264 - Wash hands and face thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
 P302 - IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
 P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
 P308+313 - IF exposed or concerned: Get medical advice/attention.
 P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
 P332 + P313 - If skin irritation occurs: Get medical advice/attention.
 P337 - If eye irritation persists: Get medical advice/attention.
 P361 + P364 - Take off immediately all contaminated clothing and wash it before reuse.
 P403+233 - Store in a well ventilated place. Keep container tightly closed.
 P405 - Store locked up.
 P410+412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
 P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Inhalation, ingestion, eye, skin
Target Organs: May cause damage to organs through prolonged or repeated exposure.
Inhalation: May cause nasal and respiratory irritation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin Contact: May cause skin irritation.
Eye Contact: May cause serious eye irritation.
Ingestion: Harmful or fatal if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

3

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
110-54-3	20-30%	Hexane
67-64-1	20-30%	Acetone
74-98-6	15-20%	Propane
106-97-8	5-10%	Butane

4

FIRST AID MEASURES

Inhalation: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
Skin Contact: Wash with plenty of soap and water. If skin irritation or rash occurs get medical attention. Take off contaminated clothing and wash it before reuse.
Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Ingestion: Harmful or fatal if swallowed. Seek medical attention immediately. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

DANGER. Extremely flammable. Contents under pressure. Harmful or fatal if swallowed. Aspiration hazard if swallowed.

Vapor harmful. Keep away from heat and flame. Can cause nervous system depression.

Stick It

SDS Number: A215A

Revision Date: 6/30/2023

Page 3 of 13

5

FIRE FIGHTING MEASURES

Flammability: Extremely flammable
Flash Point: < 0 F (liquid portion)
Flash Point Method: Not available
 Suitable fire extinguishing media: Use water spray, fog or foam.

Specific hazards arising from the chemical: Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products: Carbon Dioxide, Carbon Monoxide

Specific fire-fighting methods: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire fighters: Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

6

ACCIDENTAL RELEASE MEASURES

Personal precautions:

Put on appropriate personal protective equipment (see section 8)

Environmental precautions and clean-up methods:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

7

HANDLING AND STORAGE

Handling Precautions: Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120 F may cause bursting. Do not puncture or incinerate container.

Level 3 Aerosol.

Storage Requirements: Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

Level 3 Aerosol.

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Personal Protective Equipment:

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: When respiratory protection is required use an organic vapor cartridge. A respiratory program that

Stick It

SDS Number: A215A

Revision Date: 6/30/2023

Page 4 of 13

meets OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements must be followed.

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Hexane cas#:(110-54-3) [20-30%]

Components with workplace control parameters

TWA 50 ppm USA. ACGIH Threshold Limit Values
(TLV)

Central Nervous System impairment

Eye irritation

Peripheral neuropathy

Substances for which there is a Biological Exposure Index or Indices
(see BEI section)

Danger of cutaneous absorption

TWA 50 ppm USA. NIOSH Recommended
180 mg/m³ Exposure LimitsTWA 500 ppm USA. Occupational Exposure Limits
1,800 mg/m³ (OSHA) - Table Z-1 Limits for Air
ContaminantsThe value in mg/m³ is approximate.TWA 50 ppm USA. OSHA - TABLE Z-1 Limits for
180 mg/m³ Air Contaminants - 1910.1000

Acetone cas#:(67-64-1) [20-30%]

Components with workplace control parameters

TWA 500 ppm USA. ACGIH Threshold Limit Values
(TLV)

Eye & Upper Respiratory Tract irritation

Central Nervous System impairment

Hematologic effects

Substances for which there is a Biological Exposure Index or Indices
(see BEI section)

Not classifiable as a human carcinogen

STEL 750 ppm USA. ACGIH Threshold Limit Values
(TLV)

Eye & Upper Respiratory Tract irritation

Central Nervous System impairment

Hematologic effects

Substances for which there is a Biological Exposure Index or Indices
(see BEI section)

Not classifiable as a human carcinogen

STEL 1,000 ppm USA. OSHA - TABLE Z-1 Limits for
2,400 mg/m³ Air Contaminants - 1910.1000The acetone STEL does not apply to the cellulose acetate fiber
industry. It is in effect for all other sectors.

Stick It

SDS Number: A215A

Revision Date: 6/30/2023

Page 5 of 13

TWA 1,000 ppm USA. Occupational Exposure Limits
2,400 mg/m3 (OSHA) - Table Z-1 Limits for Air
Contaminants

The value in mg/m3 is approximate.

TWA 250 ppm USA. NIOSH Recommended
590 mg/m3 Exposure Limits

TWA 750 ppm USA. OSHA - TABLE Z-1 Limits for
1,800 mg/m3 Air Contaminants - 1910.1000

Propane cas#:(74-98-6) [15-20%]

Components with workplace control parameters

TWA 1,000 ppm USA. ACGIH Threshold Limit Values
(TLV)

Central Nervous System impairment
Cardiac sensitization

TWA 1,000 ppm USA. Occupational Exposure Limits
1,800 mg/m3 (OSHA) - Table Z-1 Limits for Air
Contaminants

The value in mg/m3 is approximate.

TWA 1,000 ppm USA. OSHA - TABLE Z-1 Limits for
1,800 mg/m3 Air Contaminants - 1910.1000

TWA 1,000 ppm USA. NIOSH Recommended
1,800 mg/m3 Exposure Limits

Butane cas#:(106-97-8) [5-10%]

Components with workplace control parameters

TWA 800 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
1,900 mg/m3 1910.1000

TWA 1,000 ppm USA. ACGIH Threshold Limit Values (TLV)

TWA 1,000 ppm USA. ACGIH Threshold Limit Values (TLV)
Central Nervous System impairment Cardiac sensitization

TWA 800 ppm USA. NIOSH Recommended Exposure Limits
1,900 mg/m3

Also see specific listing for Isobutane.

9	PHYSICAL AND CHEMICAL PROPERTIES
----------	---

Appearance:	Clear spray/ mist/aerosol	Odor:	Solvent
Physical State:	Liquid	Solubility:	Insoluble in water
Spec Grav./Density:	(H20=1): 0.8 estimated	Flash Point:	< 0 F (liquid portion)
Boiling Point:	Not available		

Stick It

SDS Number: A215A

Revision Date: 6/30/2023

Page 6 of 13

Flammability: Extremely Flammable **VOC:** 55 wt%
Vapor Pressure: Not available

10

STABILITY AND REACTIVITY

Reactivity: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical Stability: Stable under normal conditions.
Conditions to Avoid: High temperatures, open flames, sparks, welding.
 Vapors may ignite at temperatures exceeding flash point.
Materials to Avoid: Acids and strong oxidizers
Hazardous Decomposition: CO, CO₂
Hazardous Polymerization: Does not occur.

11

TOXICOLOGICAL INFORMATION

Primary Route of Entry: Skin contact, inhalation

Acute/Potential Health Effects:

EYES: May cause serious eye irritation. Symptoms include stinging, tearing and redness.

SKIN: May cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying of skin and skin burns.

INHALATION: High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage.

INGESTION: Harmful or fatal if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

Chronic / Long Term Effects: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Signs and Symptoms of Overexposure: Signs and symptoms of overexposure to this material through breathing, swallowing, and/or passage of material through the skin may include: stomach or intestinal upset (nausea vomiting, diarrhea) irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

Target Organ Effects: Central nervous system.

Reproductive/Developmental Information: Suspected of damaging fertility or the unborn child.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

Hexane cas#:(110-54-3) [20-30%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 25,000 mg/kg

LC50 Inhalation - rat - 4 h - 48000 ppm

Dermal: no data available

Stick It

SDS Number: A215A

Revision Date: 6/30/2023

Page 7 of 13

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: Eyes - rabbit Result: Mild eye irritation

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

Carcinogenicity - rat - Inhalation:

Tumorigenic: Carcinogenic by RTECS criteria. Tumorigenic Effects: Testicular tumors.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Overexposure may cause reproductive disorder(s) based on tests with laboratory animals. Suspected human reproductive toxicant Suspected of damaging fertility.

Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure: Ingestion - May cause damage to organs through prolonged or repeated exposure. - Nervous system

Aspiration hazard: May be fatal if swallowed and enters airways.

Additional Information:

RTECS: MN9275000

Prolonged or repeated contact with skin may cause: defatting, Dermatitis, Contact with eyes can cause: Redness, Blurred vision, Provokes tears., Effects due to ingestion may include: Gastrointestinal discomfort, Central nervous system depression, Lung irritation, chest pain, pulmonary edema, giddiness, slowed reaction time, slurred speech, Headache, Dizziness, Drowsiness, Unconsciousness

Testes. - Irregularities - Based on Human Evidence

Acetone cas#:(67-64-1) [20-30%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 5,800 mg/kg Remarks: Behavioral: Altered sleep time (including change in righting reflex).

Stick It

SDS Number: A215A

Revision Date: 6/30/2023

Page 8 of 13

Behavioral:Tremor.

LC50 Inhalation - rat - 8 h - 50,100 mg/m³

Inhalation: no data available

LD50 Dermal - guinea pig - 7,426 mg/kg

Skin corrosion/irritation: Skin - rabbit Result: Mild skin irritation - 24 h

Serious eye damage/eye irritation: Eyes - rabbit Result: Eye irritation - 24 h

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: AL3150000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence

Propane cas#:(74-98-6) [15-20%]

Information on toxicological effects

Acute toxicity: no data available

Inhalation: no data available

Stick It

SDS Number: A215A

Revision Date: 6/30/2023

Page 9 of 13

Dermal: no data available

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: TX2275000

Dizziness, Drowsiness, Unconsciousness

Butane cas#:(106-97-8) [5-10%]

Information on toxicological effects

Acute toxicity:

Oral LD50 no data available

Inhalation LC50 LC50 Inhalation - rat - 4 h - 658,000 mg/m³

Dermal LD50

Other information on acute toxicity

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Stick It

SDS Number: A215A

Revision Date: 6/30/2023

Page 10 of 13

Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):
no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation.

Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Central nervous system depression, giddiness, Shortness of breath, narcosis, Dermal contact with rapidly evaporating liquid could result in freezing of the tissues or frostbite., Exposure can cause numbness, tingling, and weakness in extremities., Cyanosis, Pulmonary edema. Effects may be delayed., Abdominal pain, Nausea, Vomiting

Synergistic effects: no data available

Additional Information:

RTECS: EJ4200000

Hexane cas#:(110-54-3) [20-30%]

Information on ecological effects

Stick It

SDS Number: A215A

Revision Date: 6/30/2023

Page 11 of 13

Toxicity:

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 2.5 mg/l - 96.0 h.

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 3,878.00 mg/l - 48 h.
other aquatic invertebrates

Toxicity to algae EC50 - Chlorella vulgaris (Fresh water algae) - 12,840.00 mg/l - 3 h.

EC50 - SKELETOMA - 0.30 mg/l - 8 h

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.

Acetone cas#:(67-64-1) [20-30%]

Information on ecological effects

Toxicity: no data available

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 13,500.00 mg/l - 48 h.

other aquatic invertebrates

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

Propane cas#:(74-98-6) [15-20%]

Information on ecological effects

Toxicity: no data available

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

Butane cas#:(106-97-8) [5-10%]

Information on ecological effects

Toxicity: no data available

Stick It

SDS Number: A215A

Revision Date: 6/30/2023

Page 12 of 13

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

13

DISPOSAL CONSIDERATIONS

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

14

TRANSPORT INFORMATION

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN number	1950
Proper shipping name	Aerosols, flammable
Class	2.1
Packing group	-

15

REGULATORY INFORMATION

 [%] RQ (CAS#) Substance - Reg Codes

[20-30%] RQ(5000LBS), Hexane (110-54-3) CERCLA, HAP, MASS, OSHAWAC, PA, SARA313, TSCA, TXAIR

[20-30%] RQ(5000LBS), Acetone (67-64-1) CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, TOXICRCRA, TSCA, TXAIR, TXHWL

[15-20%] Propane (74-98-6) MASS, NJHS, OSHAWAC, PA, TSCA, TXAIR

[5-10%] Butane (106-97-8) MASS, NJHS, OSHAWAC, PA, TSCA, TXAIR

WARNING

This product can expose you to chemicals including n-Hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Regulatory Code Legend

RQ = Reportable Quantity
 CERCLA = Superfund clean up substance
 HAP = Hazardous Air Pollutants
 MASS = MA Massachusetts Hazardous Substances List
 OSHAWAC = OSHA workplace Air Contaminants
 PA = PA Right-To-Know List of Hazardous Substances
 SARA313 = SARA 313 Title III Toxic Chemicals
 TSCA = Toxic Substances Control Act
 TXAIR = TX Air Contaminants with Health Effects Screening Level
 NJHS = NJ Right-to-Know Hazardous Substances
 TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)
 TXHWL = TX Hazardous Waste List

Stick It

SDS Number: A215A

Revision Date: 6/30/2023

Page 13 of 13

16

OTHER INFORMATION

Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

N/A = Not available N/D = Not determined

Revision Date: 6/30/2023