Thread Seal is a premium Teflon® enhanced compound which provides superior sealing for most threaded metal or plastic pipe. Thread Seal will prevent leaks and seal most common fluids and gases. including fuels, oils, water, refrigerants, steam and inert gases. Non-hardening formula will not crack, shred or contaminate most systems. Eases assembly and disassembly of metal and plastic fittings.

Thread Seal will not damage most plastic fittings. Seals to bursting pressure of pipe and is rated to 10,000 psi.

SUGGESTED APPLICATIONS

Plumbers "pipe dope" replaces Teflon® tape, HVAC preferred. Use Teflon® sealant on pipe threaded joints 1/4" and larger. Temperature rating of -30°F to 500°F.

DIRECTIONS

Always refer to Safety Data Sheet (SDS) and precautions on right side panel for safety information.

- 1. Clean and dry pipe threads.
- 2. Apply Thread Seal onto male threads with stiff bristle brush.
- 3. Assembly parts.
- 4. To avoid contamination, close container when not using.



Thread Seal



Pipe Sealing Paste with PTFE

SOLVENT - FREE NON-SHRINKING PREVENTS GALLING &

WARNING

KEEP OUT OF REACH OF CHILDREN FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY. (SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

NET WT 8 OZ (227G)

5/15



WARNING: May be harmful if swallowed. Causes skin irritation. May be harmful if inhaled. Causes eye irritation. Wash hands thoroughly after handling.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or a rash occurs: Get medical advice/attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. IF exposed or concerned: Get medical advice/attention.

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

WECHEM. INC. 5734 Susitna Dr. Harahan, LA 70123 504.733.1152 1.800.426.0512 FAX 504.733.2218 www.wechem.com

