

*One Step Seal & Finish · Exceptionally Long Wearing · Non-Yellowing  
Slip & Scuff Resistant · Super High Density · Highly Resistant to Soil*

**SLIP RESISTANCE (ASTM D2047) SOIL RESISTANCE (ASTM D3206)**  
**RECOATABILITY (ASTM D3153) REMOVABILITY (ASTM D1792)**  
**DETERGENT RESISTANCE (ASTM D3207)**

#### DESCRIPTION:

**ULTRA GLOSS** is a remarkable new metal cross linked floor finish. This complete product seals and finishes in one easy step. Especially suited for non-resilient floors, this product excels with use on terrazzo, quarry tile, brick, slate, Mexican tile, concrete and other floors. **ULTRA GLOSS** is also perfect for use on all resilient floors, including: asphalt tile, ceramic tile, linoleum, rubber, sealed wood, vinyl and vinyl asbestos tile.

#### DIRECTIONS:

**Floor Preparations:** Strip floor of old finish and wax, paying particular attention to baseboards, corners, under furniture, and built up areas. Rinse thoroughly and allow to dry.

**Application:** Using a clean mop or applicator, apply a thin uniform coat of finish. Avoid excessive agitation and do not allow material to dry in puddles. Apply 3 to 5 coats. Make sure finish is completely dry before applying additional coats.

**Spray Buff:** To restore original luster, spray buff with an approved formula.

**High Speed Burnishing:** This is an ideal product for use with a high speed burnishing machine of 1000 RPM or higher. The floor should be damp mopped with a suitable neutral cleaner and allowed to dry. The surface may then, as desired, be dry burnished with a high speed white or tan buffing pad, or using the same equipment, be spray buffed using **Buff-N-Shine**. An alternative method of insuring a long lasting durable surface, would be to apply **Revive** mop-on restorer, allow to dry and then follow the dry buffing procedure.

**Maintenance:** Maintain in the conventional manner by cleaning with a treated yarn dust mop to remove surface dirt daily. Damp mop or clean with an automatic scrubber as required, using an approved neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended. Worn areas, or the entire floor, may be recoated as required to maintain a uniform high gloss. When stripping becomes necessary, use **MOP OFF** according to label directions.



Engineered Chemistries  
**SUPERIOR SOLUTIONS**

# ULTRA GLOSS™

## “Wet Look” Floor Finish High Speed Burnishing



### WARNING

KEEP OUT OF REACH OF CHILDREN.  
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.  
SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.

**NET CONTENTS: 2.5 U.S. GALLONS**

Rev. 12.2023



#### WARNING

**Causes mild skin irritation. Causes eye irritation.  
May cause respiratory irritation. Harmful to aquatic  
life with long lasting effects.**

**If Swallowed:** Do not induce vomiting.

**If On Skin:** Wash with soap and water.

**If In Eyes:** Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

**If Inhaled:** Remove to fresh air. If breathing is difficult give oxygen.

READ SAFETY MATERIAL DATA SHEET BEFORE USE.

SCAN FOR SDS



**MADE IN THE USA**

WECHEM, INC.  
5734 Susitna Dr  
Harahan, LA 70123  
504.733.1152  
800.426.0512  
FAX 504.733.2218  
www.wechem.com

