



**DANGER:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. May cause respiratory irritation.

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection, and face protection. Do not breathe the mist, vapors, or spray. Use only outdoors or in a well-ventilated area.

**IF exposed or concerned:** Get medical attention. Get medical attention if you feel unwell.

**IF SWALLOWED:** Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F. Store locked up. Store in a well-ventilated place. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Please refer to the SDS for additional information. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. Percentage of the mixture consisting of ingredient(s) of unknown toxicity: oral 13.6%, dermal 13.6%, inhalation 13.6%.

**CONTAINS [CAS#]:** Mineral Oil, Petroleum Distillates Hydrotreated (Mild) Heavy Naphthenic [64742-52-5], Paraffin Oil [64742-62-7], Propane [74-98-6], Butane [106-97-8], Coconut Diethanolamide [68603-42-9].

**WARNING:** This product can expose you to chemicals including coconut diethanolamide, which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**WECHEM®**  
Engineered Chemistries  
SUPERIOR SOLUTIONS

# WIREF COAT

## Foaming Chain & Cable LUBRICANT PROTECTANT

- Contains "Moly"
- Thick Clinging
- Penetrates, Lubricates Foam
- Form Protective Rust Barrier Foam

**DANGER. EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED; MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. SUSPECTED OF CAUSING CANCER. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. MAY CAUSE DROWSINESS OR DIZZINESS. MAY CAUSE RESPIRATORY IRRITATION.**

READ CAREFULLY OTHER CAUTIONS ON BACK PANEL.

**NET WT. 16 OZ. (1LB.) (453 grams) 12/21**

Fortified with Moly\*- Chain and Cable lube provides superior penetrating action to rollers, pins, links and bushings of chains. Leaves a lubricating film, which reduces friction, wear and corrosion. When applied to wire ropes and cables, the Moly and other additives plate the strands to provide anti-wear and rust protections. \*Moly is molybdenum disulfide- a chemical compo with the symbol MoS2.

### DESCRIPTION

Moly containing lubricant that protects parts which are exposed to harmful or corrosive elements. Lubricates and penetrates to protect against friction and wear.

### FEATURES AND BENEFITS

Thick foam that clings to gears, chains and wire ropes. As foam breaks, product penetrates into wire ropes, links, and roller mechanisms. Provides resistance to wear. Extreme pressure capability. Will not break down under high temperatures. Forms a protective rust barrier.

### APPLICATIONS AND USES

Recommended for use in severe climatic conditions. For use on gears, chains, cables, sprockets, power drive hoists, motorcycles, bicycles, chain saws, wire ropes, link and roller assemblies, material handling equipment, road and construction machinery.

### DIRECTIONS FOR USE

Shake well before using. Spray 8 to 10 inches from surface. Allow to penetrate. Second coat gives additional protection.

**USED BY:** Industrial Facilities, Shipyards, Steel Mills, Aircraft Maintenance, Materials Handling, Road Equipment, Construction, Mining, Containerized Shipping Companies.

**Caution:** Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

**KEEP OUT OF REACH OF CHILDREN.**

See Safety Data Sheet for complete safety information.  
24 HOUR MEDICAL EMERGENCY: 1-800-535-5053.  
CONTAINS NO OZONE DEPLETING CHEMICALS!

**WEICHEM, INC.**

5734 Susitna Dr. Harahan, LA 70123

504.733.1152 · 1.800.426.0512

FAX 504.733.2218 · [www.wechem.com](http://www.wechem.com)

