

DANGER

Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

FIRDT AID

IF SWALLOWED: If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

IN ON SKIN: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek immediate medical attention. Do not use solvents to remove oil.

IF INHALED: Move to fresh air. If breathing difficulty persists, seek medical attention.

IF IN EYES: Immediately flush with water for 15 minutes while holding eyelids open. Seek medical attention if irritation persists.


CONTAINS (CAS#): Heavy Naphthenic Petroleum Distillate (64742-52-5), Propane/n-Butane (68476-86-8), Stoddard Solvent (8052-41-3).

Warning: This product can expose you to chemicals including Ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

KEEP OUT OF REACH OF CHILDREN.

See Safety Data Sheet for complete safety information.

Emergency Telephone Number: INFOTRAC 1-800-535-5053



Penetrates into Cables & Chains **Protects Against Friction & Wear** Will Not Attract Dust & Dirt **Protects Against Rust & Corrosion**

WIRE COAT™ is a high speed chain and cable lubricant with moly is specially designed to provide maximum protection to wire ropes and chains of all types. This product will completely penetrate into the strands of wire ropes providing the ultimate in lubrication. This product will not build up on chains to attract dust or dirt, but will provide complete lubrication on rollers, pins and bushings. Continued use of this product reduces chain whip, vibration and noise, also protects against galling, seizing and wear, thus adds life to chain cable and sprockets.

FOR USE ON: Chains, Wire Cable, Open Gears, Sprockets, Chain Saws, Drag Lines, Power Drives, Fittings, Booms, Road and Construction Machinery, Hoists, Winches, Cranes, Material Handling Equipment, Tow Lines, Linkages and Roller Assemblies.

DIRECTIONS:

Shake well. Surface to be sprayed should be clean and dry. Remove protective cap. Hold container 6-12 inches from surface to be treated. Point opening in desired direction. Press button to spray.





To Reorder: WECHEM, INC. 5734 Susitna Dr. Harahan, LA 70123 504.733.1152 www.wechem.com

