

GEAR GUARD is a tacky spray lubricant that protects all moving metal surfaces from metal-to-metal contact. Forms a protective water-resistant coating to prevent corrosion in outdoor applications.

GEAR GUARD provides an elastic retractable film that reapplies itself with each revolution or movement of the lubricated part.

GEAR GUARD penetrates into gears and cables where it sets up and bonds to parts, maintaining a cushion of lubricant between gear teeth and other friction-producing surfaces. Absorbs high shock loads, extreme pressure and prevents chipping and scuffing. Will not wash off, dry out, crack or peel.

USE ON:

Passenger and freight elevators, drag lines, construction, mining, dredging and earth moving equipment; textile and steel mill machinery, winches, cranes, tugboats, offshore drilling rigs, snow removal equipment and wherever an underwater lubricant is needed.

READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT.

DIRECTIONS: SHAKE WELL

Shake can well before using. Remove protective cap. Hold can 6 to 8 inches from surfaces to be sprayed. Apply an even coat to surface. Turn on machinery and allow lubricant to spread over all working surfaces. Apply a second thinner coating to ensure adequate lubrication. Reapply as needed to lubricate and protect equipment. After spraying, turn can upside down and spray until nozzle is clear.

See Safety Data Sheet for complete safety information.

Contains no ozone depleting chemicals!



Gear Guard™

OPEN GEAR LUBRICANT

FOR OPEN GEARS, CHAINS, CABLES, WIRE ROPES

HEAVY SERVICE TEMPERATURE RANGE +20°F TO +175°F

CONTAINS NO CHLORINATED OR FLUORINATED SOLVENTS

DANGER: EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.
See Other Cautions on Back Panel.

NET WT. 12 OZ (340 Grams)

02/23



NOT FOR SALE OR DISTRIBUTION IN CALIFORNIA

DANGER: Extremely flammable aerosol. Contains gas under pressure: May explode if heated. Causes skin irritation. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Wash hands thoroughly after handling, take off contaminated clothing and wash it before reuse. Wear protective gloves. Dispose of contents/container in accordance with local, state, and federal regulations.

IF ON SKIN: Wash with plenty of water. If skin irritation occurs, get medical advice or attention.

IF IN EYES: Immediately flush with water for 15 minutes while holding eyelids open. Seek medical attention if irritation persists.

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

CONTAINS (CAS#): Petroleum resins (64742-16-1), Distillates (petroleum), hydrotreated light (64742-47-8), Heptane (142-82-5), Propane (74-98-6), Residual oils (petroleum), solvent-dewaxed (64742-62-7).

KEEP OUT OF REACH OF CHILDREN

WEICHEM, INC.

5734 Susitna Drive • Harahan, LA 70123
504. 733.1152 • 800.426.0512
fax 504.733.2218 • www.wechem.com

SCAN FOR SDS

