

## USED FOR: DRILLS • TAPS • CUTTING TOOLS

**HYDRO CUT** is a synthetic lubricant effective in punching, drilling, tapping, sawing, machining, cutting, boring, threading and grinding operations on all steels, titanium, monel and aluminum.

### HYDRO CUT INCREASES PRODUCTION AS WELL AS TOOL LIFE RESULTS IN COOLER WORKPIECE WITH LESS TOOL BURNING

- Fluid is transparent providing better visibility of work area.
- Can be removed with cold water or degreaser solvents.
- Cools cutting tools for longer life.
- Lubricates to penetrate surface and provide a continuous non-staining film and protects from corrosion.
- Non-chlorinated

### COOLS THESE SURFACES

- Aluminum and Aluminum Alloys
- Carbon Steels
- Stainless Steels
- Chrome-Moly and Vanadium Steels
- Nitralloy Steel
- Iconel
- Monel
- Phosphor
- Bronze
- Titanium
- Hastelloy Alloys
- Beryllium
- Copper and other related alloys

### DIRECTIONS

Spray area to be worked generously. Reapply as necessary to keep work area cool and well lubricated.



Engineered Chemistries  
**SUPERIOR SOLUTIONS**

# HYDRO CUT™

## CUTTING & TAPPING FLUID

## COOLANT LUBRICANT FOR DRILLS • TAPS • CUTTING TOOLS

**DANGER:** EXTREMELY FLAMMABLE. KEEP OUT OF REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED. SEE OTHER CAUTIONS ON SIDE PANEL.

NET WT: 10 OZ (283.5 GRAMS)

4/22



**DANGER:** Extremely flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. May be harmful if swallowed and enters airways. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Keep container tightly closed. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/ vapors/spray. Wash hands thoroughly after handling. Use only outdoors or in well-ventilated area. Wear protective gloves/protective clothing/eye protection /face protection. Store in a well-ventilated place. Keep cool. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

### FIRST AID

**IF SWALLOWED:** Immediately call a POISON Center/doctor. Rinse mouth. DO NOT induce vomiting.

**IF SKIN CONTACT:** Take off immediately all contaminated clothing. Rinse skin with water (or shower). If irritated seek medical attention.

**IF INHALED:** Remove to fresh air. Resuscitate if necessary. Call a POISON CENTER/doctor if feeling unwell.

**IF EYE CONTACT:** Cause serious eye irritation. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do continue rinsing. If irritated seek medical attention.

**KEEP OUT OF REACH OF CHILDREN  
NOT FOR SALE IN CALIFORNIA**

For further information consult Safety Data Sheet.

CONTAINS:	CAS#
Isopropyl Alcohol .....	67-63-0
Distillates, petroleum, hydrotreated light .....	64742-47-8

TO REORDER: WEICHEM, INC.  
5734 SUSITNA DRIVE,  
HARAHAN, LA 70123  
504.733.1152 • FAX 504.733.2218 1  
.800.426.0512 • WWW.WEICHEM.COM

