

**• DOES NOT CONTAIN
TRICHLOROETHYLENE,
PERCHLOROETHYLENE,
OR 1-BROMOPROPANE**

FORCE 200® is an excellent energized electrical cleaner, degreaser. It dries quickly and is residue free. It quickly removes dirt, grease, wax, grime, adhesives and many other soils. High dielectric strength and non-flammability make this degreaser safe for use on energized electrical equipment while in operation such as motors, relays, switches, generators control panels, and utility cables.

FORCE 200® can be sprayed into electric equipment while in operation for complete and convenient cleaning. Helps improve electrical properties and efficiencies by removing contaminants.

FORCE 200® quickly removes sticky cable filling and flooding compounds, lubricants, gels, greases, c-cement, and other petroleum-based products from cable, splices, and utility work tools.

FORCE 200® removes water blocking compounds, carbon, and other contaminants from splices on telecom, electrical, fiber optic and CATV cables.

IDEAL FOR USE ON:

- Industrial Equipment
- Marine Equipment
- Heating & Air Conditioning Equipment
- Refrigeration Equipment
- Generators • Motors • Windings
- Gears • Utility Cables • Air Tools
- Breakers • Compressors
- Processing Equipment

*Safe on most plastics. Pretesting on small inconspicuous area is suggested on sensitive or questionable plastic surfaces before use.

DIRECTIONS:

Apply with several short bursts to remove contaminants. Continue applying with short bursts until surface is rinsed free of residue. For heavily encrusted areas, brush after initial application, then rinse off with a second application. Surface will dry in seconds. Use extension tube for hard to reach areas.

Not to be used for motorized vehicle maintenance or their parts.



Engineered Chemistries
SUPERIOR SOLUTIONS

FORCE 200®

Degreasing SOLVENT

Excellent Cable Cleaner
Non-Flammable
Fast Drying Formula
Zero Residue
Dielectric Strength of
35,000 Volts

WARNING:

CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

See back panel for additional cautions.

NET WT. 18 OZ. (1 LB. 2 OZ.) 510g

3/22



WARNING:

Contains gas under pressure; may explode if heated. Harmful if swallowed or inhaled. Avoid breathing spray. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Do not eat, drink, or smoke when using this product. Protect from sunlight. Store in a well-ventilated place. Dispose of container in accordance with local regulations.

IF SWALLOWED: Call a poison control center if you feel unwell. Rinse mouth.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison control center if you feel unwell.

Contains: Trans-1,2-Dichloroethylene (156-60-5), Proprietary fluorinated Solvents, and Carbon Dioxide (124-38-9).

Warning: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120° F(49°C). Chemical contact with flames or extremely hot surfaces may lead to the formation of dangerous decomposition products.

KEEP OUT OF REACH OF CHILDREN.

See Safety Data Sheet for complete safety information. 24 HOUR MEDICAL EMERGENCY: 1-800-535-5053. CONTAINS NO OZONE DEPLETING CHEMICALS.

Not for sale or distribution in CA, UT, OTC or LADCO states.

To Reorder:

WEICHEM, INC.
5734 Susitna Drive
Harahan, LA 70123
504.733.1152
FAX 504.733.2218
800.426.0512
www.wechem.com

