

MEETS MIL-907D Dry Moly Film Lubricant and Coating is a superior, long-lasting dry lubricant that withstands high temperatures and pressures. Repels dust and dirt and is resistant to water, alkalis and most acids. Prevents corrosion, seizing, wear binding, squeaking and scraping. Withstands temperature ranges from -78°C to 316°C (-110°F to +600°F). Resists pressure up to 100,000 psi. Contains pure Molybdenum Disulfide micro-particles which burnish themselves into metal surfaces and provide a bonded dry lubricating film.

INDUSTRIAL APPLICATIONS:

Oil Drilling Equipment, Foundries, Automotive Plants, Vehicle Maintenance, Sewing Trades, Paper and Corrugated Converting, Chemical Plants, Woodworking, Marine, Agricultural & Military Equipment, Road Equipment, Aircraft Maintenance, Steel Mills and Mining Operations.

DIRECTIONS:

Shake can vigorously before application. Surface must be clean and dry prior to application. Hold can 8 to 10 inches from surface and spray in a sweeping motion to insure a thin uniform coating. Allow to set approximately 3 to 5 minutes before applying second coat. **IMPORTANT:** To prevent clogging, after each use, invert can and spray a few short bursts to clear valve.

See Safety Data Sheet for complete safety information.

24 HOUR MEDICAL EMERGENCY: 1-800-535-5053.

CONTAINS NO OZONE DEPLETING CHEMICALS!

KEEP OUT OF REACH OF CHILDREN.

WECHEM, INC.

5734 Susitna Dr. Harahan, LA 70123

504.733.1152 · 1.800.426.0512

FAX 504.733.2218 · www.wechem.com



Engineered Chemistries
SUPERIOR SOLUTIONS™

MOLY D

FILM LUBRICANT & COATING

Non-Chlorinated
Anti-Friction
Anti-Seize
Non-Corrosive
Non-Conductive
Waterproof

DANGER:

**EXTREMELY FLAMMABLE,
HARMFUL OR FATAL IF SWALLOWED.
EYE AND SKIN IRRITANT,
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON SIDE PANEL.**

NET WT. 11oz/312g



DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avioderelase to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and was before reuse. Store in a well ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local/regional/national/international regulations.

FIRST AID: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. DO NOT induce vomiting. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. **IF ON SKIN:** Wash with plenty of soap and water. Wash contaminated clothing before use. Get medical attention. **IF INHALED:** Remove victim to fresh air and comfortable for breathing. **IF IN EYES:** Rinse continuously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye Irritation persists: Get medical advice/attention. **IF exposed or concerned:** Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. Specific treatment (see this label).

CONTAINS: Acetone (67-64-1), Propane (74-98-6), Isopropanol (67-63-0), Methyl acetate (79-20-9), Butane (106-97-8),