

**NON-FLAMMABLE
NON-CONDUCTIVE
NON-CHLORINATED
FOUR WAY PROTECTION
PREVENTS RUST
DISPLACES MOISTURE**

PENETRATES through rust and scale to loosen parts which have been frozen by corrosion. **LUBRICATES** parts to ensure free and easy movement. **DEMOISTURIZES** and creates a waterproof film that dries out electrical equipment, inhibits corrosion, and prevents electrical discharge. **PROTECTS** and creates a non-drying film that seals parts against atmospheric and mild corrosion.

DIRECTIONS:

TO REMOVE CORROSION: Spray liberally directly onto dirt and scale. Allow to penetrate. Remove loosened scale, then reapply to leave an anti-corrosion coating.

TO DISPLACE MOISTURE: Spray electrical equipment until thoroughly saturated. Allow to penetrate before attempting to restart, then reapply to protect surfaces.

TO LOOSEN FROZEN NUTS AND BOLTS: Apply liberally to frozen nuts and bolts, hinges, and sliding and rotating parts. Allow to penetrate into threads. Work back and forth, then reapply to leave a never-dry, protective lubricating film.

IDEAL FOR USE ON:

- Locks / Hinges
- Guns
- Nuts / Bolts
- Sockets
- Tools
- Rollers
- Rods / Reels
- Breakers
- Distributors
- Batteries
- Electrical Motors
- Electrical
- Wet Engine Contacts



Engineered Chemistries
SUPERIOR SOLUTIONS

TRIO

Multi-Use Mechanical Spray

**Penetrating Lubricant
Prevents Rust
Displaces Moisture
50,000V Dielectric Strength**

DANGER:

**Contains Gas Under Pressure;
May Explode If Heated.
(See Side Panels For Additional Cautions)**

NET WT: 11 OZ (312g)



DANGER

Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Suspected of damaging fertility or the unborn child. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Wear protective gloves / protective clothing / eye protection / face protection. Store locked up. Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Dispose of contents/container in accordance with local / regional / national / international regulations.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

CONTAINS: Distillates, Petroleum, Hydrotreated Light (64742-47-8), Mineral oil (8042-47-5), Cyclohexylsiloxane, octamethyl (556-67-2), Carbon dioxide (124-38-9).

KEEP OUT OF REACH FROM CHILDREN.

Emergency Telephone Number: INFOTRAC 1-800-535-5053

WEICHEM, INC.

5734 Susitna Dr. • Harahan, LA 70123

504.733.1152 • 1.800.426.0512

FAX 504.733.2218 • www.wechem.com

SCAN FOR SDS



Rev. 05.2025

