



Penetrates Lubricates Demoisturizes

**Leaves Rust Preventative Film** 

40,000 Volt Dielectric Strength Method(ASTM D877)

WARNING: VAPOR HARMFUL CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON SIDE PANEL.

- NON-FLAMMABLE
- NON-CHLORINATED
- PENETRATES & CLEANS
- FREES FROZEN FITTINGS
- LEAVES PROTECTING, NON-DRYING. WATERPROOF FILM
- DRIES OUT ELECTRICAL EQUIPMENT

PENETRATES through rust and scale to loosen parts which have been frozen by corrosion. LUBRICATES parts to ensure free and easy movement. **DEMOISTURIZES** and creates a waterproof film that dries out electrical equipment, inhibits corrosion and prevents electrical discharge. PROTECTS and creates a non-drying film that seals parts against atmospheric and mild chemical corrosion.

## **DIRECTIONS:**

### To Remove Corrosion:

Spray liberally directly onto dirt and scale. Allow to penetrate. Remove loosened scale, then reapply to leave an anti-corrosion coating.

#### To Displace Moisture:

Spray electrical equipment until thoroughly saturated. Allow to penetrate before attempting to restart, then reapply to protect surfaces.

#### To Loosen Frozen Nuts and Bolts:

Apply liberally to frozen nuts and bolts, hinges and sliding and rotating parts. Allow to penetrate into threads. Work back and forth, then reapply to leave a never-dry, protective lubricating film.

Guns

Sockets

Breakers

Batteries

Electrical

Rollers

To ensure adequate protection, reapply periodically.

# **IDEAL FOR USE ON:**

- Locks / Hinges
- Nuts / Bolts

- Tools
- Rods / Reels
- Distributors
- Wet Engine
- Contacts
- Electrical Motors





WARNING: Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not pierce or burn, even after use. Avoid breathing gas. Wear protective gloves/protective clothing/eye protection/face protection. Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.

IF EXPOSED OR CONCERNED: Get medical advice/attention.

IF IN EYES: Rinse with water for at least 15 minutes, Rmove contact lens if present and esy to do so. Continue rinsing. Get medical attention if irritation develops and persists.

IF INHALED: Move to fresh air. Call a physician if symptoms develop or persist.

IF SWALLOWED: Immediately call a POISION CENTER or doctor/physician. Rinse mouth. Do NOT induce voimiting. If voimiting occures, keep head low so that stomach content doesn't get into

CONTAINS: Distillates, Petroluem, Straight-Run Middle(64741-44-2), Ethylene Glycol Monobutyl Ether(111-46-2), Naphthalanesulfonic Acid, Dinonyl-, Zinc Salt(28016-00-4), Naphthalensulfonic Acid, Dinonyl-, Calcium Salt(57855-77-3).

Caution: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. KEEP OUT OF REACH OF CHILDREN.

See Safety Data Sheet for complete safety information. 24 HOUR MEDICAL EMERGENCY: 1-800-535-5053 CONTAINS NO OZONE DEPLETING CHEMICALS

To Reorder: WECHEM, INC. 5734 Susitna Drive Harahan, LA 70123 504.733.1152 FAX: 504.733.2218 800.426.0512 www.wechem.com



