Gel-based paint remover quickly shellac, paint, lacquer, removes carbon enamel, varnish, labels, deposits, silicone, simulated wood paneling and similar materials. Product will not run. The methylene chloride free formula is a safer alternative to paint removal.

FOR USE BY: Auto dealers, paint shops, maintenance departments, engine rebuilders, factories, furniture refinishers, painters, sign builders, schools, motels, hotels, hospitals and offices. FOR USE ON: Metal parts, plaster, concrete, tile, glass, ceramic, engine parts, valve seals, paint guns, paper, wood, stone, masonry and cylinders.



Engineered Chemistries SUPERIOR SOLUTIONS



PAINT & GASKET STRIPPER









DANGER: Highly flammable liquid and vapor. Causes severe skin burns and eve damage. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosionproof electrical / ventilating / lighting equipment. Use only non-sparking tool. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water (or shower). In case of fire: Use alcohol resistant foam, Carbon dioxide, or dry powder to extinguish. Do not breathe dust, fume, mist, vapor or spray. Wash hands with soap and water thoroughly after handling. Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Take off Immediately all contaminated clothing. Immediately rinse with water for several minutes. IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get emergency medical help immediately. Use only outdoors or in a well-ventilated place. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Obtain, read, and follow all safety instructions before use. If exposed or concerned, get medical advice. Dispose of contents and container in accordance with local, state, and national regulations.

NOT FOR SALE IN CALIFORNIA

CONTAINS (CAS#): Acetone (67-64-1), Dioxolane (646-06-0), Monoethanolamine (141-43-5), Isopropylidene Glycol (100-79-8), Dimethyl Carbonate (616-38-6).

PROPER SHIPPING NAME:

UN 1993.

Flammable Liquid,

N.O.S. (Acetone, Dioxolane), 3. PG II.



WECHEM, INC. 5734 Susitna Dr. • Harahan, LA 70123 504.733.1152 • www.wechem.com



SCAN FOR SDS



DIRECTIONS FOR USE:

Preclean accumulations of dirt and grease with a heavy duty detergent. Allow to dry. Apply undiluted compound in a full heavy coat. Allow to stand until paint is thoroughly wrinkled or bubbled. Flush with water or solvent. Use a scraper or wire brush in cracks, crevices or on stubborn accumulation. On painted floors, a squeegee may be used to move the stripper from one area to another when finished, and compound may be reused. Add new product periodically.

METHYLENE CHLORIDE FREE • MULTI-SURFACE REMOVES WIDE RANGE OF PAINTS & SEALERS FROM METAL, CONCRETE AND WOOD

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE.

NET WT: 5 U.S. GALLONS